

**MINIMUM NAILING SCHEDULE:**

1.	JOIST OR RAFTERS TO SIDES OF STUDS 8-INCH JOIST OR LESS FOR EACH ADDITIONAL 4 INCHES IN DEPTH OF JOIST	3-16d 1-16d 2-8d
2.	BRIDGING TO JOIST, TOENAIL EACH END a. BLOCKING BETWEEN JOISTS OR RAFTERS - TO JOIST OR RAFTERS - TOENAILS EACH SIDE, EACH END b. BLOCKING BETWEEN STUDS, EACH END	2-10d 2-10d toenails or 2-16d
3.	SOLE PLATE TO JOIST OR BLOCKING, FACE NAIL	16d at 16" o.c.
4.	TOP PLATE TO STUD, END NAIL	2-16d
5.	STUD TO SOLE PLATE	4-8, toenail or 2-16d, end nail
6.	DOUBLE STUDS, FACE NAIL	16d at 24" o.c.
7.	DOUBLED TOP PLATES, FACE NAIL	16d at 16" o.c.
8.	TOP PLATES, LAPS AND INTERSECTIONS, FACE NAIL	2-16d
9.	CEILING JOISTS TO PLATE, TOENAIL	3-8d
10.	CONTINUOUS HEADER TO STUD, TOENAIL	4-8d
11.	CEILING JOISTS, LAPS OVER PARTITIONS, FACE NAIL	3-16d
12.	CEILING JOISTS TO PARALLEL RAFTERS, FACE NAIL	3-16d
13.	JOIST OR RAFTERS AT ALL BEARINGS - TOENAILS, EACH SIDE	2-10d
14.	1" BRACE TO EACH STUD AND PLATE, FACE NAIL	2-8d
15.	BUILT-UP CORNER STUDS	16d at 24" o.c.