

Resources

New WOOD SOLUTION PAPER

CLT Diaphragm Design for Wind and Seismic Resistance Using SDPWS 2021 and ASCE 7-22



New CASE STUDIES

Adidas East Village Expansion

Innovative mass timber designs meet ambitious construction timeline





Thomas Logan

Wood-frame urban podium project fills need for affordable downtown housing

Visit woodworks.org/publications-media

Upcoming Events

General Contractor's Guide to Mass Timber Project Estimation | August 12


2.0 AIA/CES LUs, 2.0 PDH credits, 0.20 ICC credits

1030 Music Row Tour + Networking | August 24

1.0 AIA/CES HSW LUs, 1.0 PDH credits, 0.10 ICC credits



Visit woodworks.org/events





September 12-14 Boston, MA

Proud to Partner With

Building the Playbook for the Future of Taller, More Innovative Timber Structures

www.advancing-mass-timber.com

Mass Timber Business Case Studies

Real financial information on real deals

- Prepared by WoodWorks and Conrad Investment Management
- Include qualitative influences + quantitative data to examine investment success

PROPERTY SUB-TYPES:

For-Rent Institutional Housing • Institutional Offices • Industrial Buildings • Redevelopment/Additions • Purpose-Built Owner/Occupied (Student Housing)



WOODWORKS

Quantitative Overview



« Scan the code to download the current package.

New for GCs and installers:

U.S. Mass Timber Construction Manual





Download free at woodworks.org

TO: MARGUS KAUPPMAN



Nominations Open

Visit woodworks.org/nominate

2023 Wood Design Awards

DEADLINE: OCT. 14, 2022



Design Professionals:

One-on-One Support & Assistance

PROJECT SUPPORT FIELD DIVISION



Meet the **Help Desk**











Ashley Cagle, PE, SE

Karen Gesa, PE

Bruce Lindsey



Melissa Kroskey, AIA, SE



Terry Malone, PE, SE



Ricky McLain, PE, SE

Need technical assistance on a project? Email: help@woodworks.org

NOW HIRING







visit woodworks.org/careers



Continuing Education Credits


- Participants will receive a certificate of completion via email
- AIA credits will be processed by WoodWorks

 To receive credit and a certificate, attendees must stay on for the duration of the seminar.

Ask Questions through the Q&A Box



Submit questions in the Q&A box at the bottom of your screen as they come up in the presentations. We will get to as many questions as possible.



Questions? Ask us anything.



Jessica Scarlett
Regional Director | NC, SC, TN

(803) 616-6231 jessica.scarlett@woodworks.org



Warren Hamrick

Engineered Wood Specialist

(828) 289-7012

warren.hamrick@apawood.org





Allowable Building Size

IBC Chapter 5

Allowable building size a function of:

- » Building use (occupancy)
- » Construction type
- » Fire department access
- » Sprinklers



Occupancy Groups

IBC Chapter 3

Mixed use buildings often have 2, 3 or more different occupancy groups. Common examples include:

A: Assembly: restaurant, theater, arena, lecture hall

B: Business: office building, college, bank

M: Mercantile: retail store, sales room

R: Residential: apartment, dormitory, hotel

S: Storage: parking, bulk material storage

Construction Types

IBC 602

Type III

Exterior walls non-combustible (may be FRTW) Interior elements any allowed by code

Type V

All building elements are any allowed by code

Types III and V are subdivided into A (protected) and B (unprotected)

Type IV (Heavy/Mass Timber)

Exterior walls non-combustible (may be FRTW)
Interior elements qualify as Heavy Timber (min. sizes, no concealed spaces)

Construction Types

Allowable Building Height

IBC 2018 Tables 504.3 & 504.4

TABLE 504.3
ALLOWABLE BUILDING HEIGHT IN FEET ABOVE GRADE PLANE®

OCCUPANCY CLASSIFICATION	TYPE OF CONSTRUCTION									
	SEE FOOTNOTES	TYPE I		TYPE II		TYPE III		TYPE IV	TYP	E V
	011.0010120	Α	В	Α	В	Α	В	нт	Α	В
A, B, E, F, M, S, U	NS ^b	UL	160	65	55	65	55	65	50	40
	S	UL	180	85	75	85	75	85	70	60

TABLE 504.4
ALLOWABLE NUMBER OF STORIES ABOVE GRAD E PLANE®. b

OCCUPANCY CLASSIFICATION				TYPE OF	CONST	UCTION				
	SEE FOOTNOTES	TYPE I		TYPE II		TYPE III		TYPE IV	TY	PE V
		A	В	A	В	A	В	нт	A	В
A 1	NS	UL	5	3	2	3	2	3	2	1
A-1	S	UL	6	4	3	4	3	4	3	2
B	NS	UL	11	5	3	5	3	5	3	2
В	S	UL	12	6	4	6	4	6	4	3
Б	NS	UL	5	3	2	3	2	3	1	1
E	S	UL	6	4	3	4	3	4	2	2

Construction Types

Allowable Building Area

IBC 2018 Table 506.2

TABLE 506.2
ALLOWABLE AREA FACTOR (A, = NS, S1, S13R, S13D or SM, as applicable) IN SQUARE FEET^{a, b}

		TYPE OF CONSTRUCTION											
OCCUPANCY CLASSIFICATION	SEE FOOTNOTES	TYP	ΕI	TYPE II		TYPE III		TYPE IV	TYP	PE V			
		Α	В	Α	В	Α	В	HT	Α	В			
	NS	UL	UL	15,500	8,500	14,000	8,500	15,000	11,500	5,500			
A-1	S1	UL	UL	62,000	34,000	56,000	34,000	60,000	46,000	22,000			
	SM	UL	UL	46,500	25,500	42,000	25,500	45,000	34,500	16,500			
	NS	UL	UL	37,500	23,000	28,500	19,000	36,000	18,000	9,000			
В	S1	UL	UL	150,000	92,000	114,000	76,000	144,000	72,000	36,000			
	SM	UL	UL	112,500	69,000	85,500	57,000	108,000	54,000	27,000			
	NS	UL	UL	26,500	14,500	23,500	14,500	25,500	18,500	9,500			
Е	S1	UL	UL	106,000	58,000	94,000	58,000	102,000	74,000	38,000			
	SM	UL	UL	79,500	43,500	70,500	43,500	76,500	55,500	28,500			


Construction Type Differences

	IIIA	IIIB	IV	VA	VB
Ext Wall Material	FRTW	FRTW	FRTW	Any wood	Any wood
Ext Bearing Wall Rating	2 Hr	2 Hr	2 Hr	1 Hr	0 Hr
Interior Elements	Any wood	Any wood	Heavy Timber	Any wood	Any wood
Fire Wall Materials	Non- combustible	Non- combustible	Non- combustible	Any	Any
Building Size	Typ 2 nd largest; often same # of stories as IV but smaller area	Comparable to VA, larger in some cases, smaller in others	Typ largest; often same # of stories as IIIA but larger area	Comparable to IIIB; often 1-2 stories less than IIIA and IV	Smallest; often 1 story less than VA and 1/2 to 2/3 area of VA

Fire Department Access

IBC 202

Mid-Rise vs. High-Rise



High-Rise Building:

A building with an occupied floor located more than 75 feet above the lowest level of fire department vehicle access.


FIGURE 6-6 Determination of high-rise building

Fire Department Access

IBC 506

Frontage

Frontage provides access to the structure by fire service personnel, a temporary refuge area for occupants as they leave the building in a fire emergency and a reduced exposure to and from adjacent structures. Larger building area possible with certain amount of frontage



Sprinkler Requirements

IBC 903.2



- » NFPA 13 or 13R sprinkler system required in all new group R fire areas
- » NFPA 13 sprinkler system required in most commercial facilities of any size regardless of construction type or materials used
- » Example: Occupancy Group A-2 (restaurant, casino, banquet hall):
 - » If Fire Area Exceeds 5,000 sf, or
 - » If occupant load is 100 or more

Commercial Sprinkler Systems

IBC 903.3.1

» NFPA 13

Standard for Commercial Construction 903.3.1.1

» NFPA 13R

Residential Occupancies (Oneand Two-Family or Low-Rise Multi-Family and Commercial) 903.3.1.2

» NFPA 13D


Standard for One- and Two-Family Residences (but allowed in a few commercial occupancies) 903.3.1.3








Sprinkler Differences





Goal: Provide life safety and property protection	Goal: Provide life safety only
Fully sprinklered system throughout entire building even in unoccupied spaces (closets, attics)	Partially sprinklered system; unoccupied spaces often don't require sprinklers
Can cost more	Lower levels of water discharge, shorter water supply time can result in smaller pipe sizes, reduce need for storage & pumps
Permitted for many occupancies, buildings of many sizes, allows greater building size increases	Limited applications, mainly for multi-family up to 4 stories, 60 feet


Allowable Building Height

IBC 2018 Tables 504.3 & 504.4

Building Height Increase

Buildings equipped throughout with an NFPA 13 or 13R* sprinkler system are allowed an additional **1 story and 20 ft** over nonsprinklered conditions

*NFPA 13R limited to 60 ft & 4 stories



Allowable Building Height

IBC 2018 Table 504.3

Provides base (non-sprinklered) & increased heights

TABLE 504.3"
ALLOWABLE BUILDING HEIGHT IN FEET ABOVE GRADE PLANE

	TYPE OF CONSTRUCTION											
OCCUPANCY CLASSIFICATION	SEE FOOTNOTES	TYPEI		TYPEII		TYPE III		TYPE IV	TYPE V			
		Α	В	А	В	A	В	нт	Α	В		
	NS ^b	UL	160	65	55	65	55	65	50	40		
A, B, E, F, M, S, U	S	UL	180	85	75	85	75	85	70	60		
	NS ^{d, b}	UL	160	65	55	65	55	65	50	40		
R	S13R	60	60	60	60	60	60	60	60	60		
	S	UL	180	85	75	85	75	85	70	60		

NS = Buildings not equipped throughout with an automatic sprinkler system

S = Buildings equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.1 (NFPA 13)

S13R = Buildings equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.2 (NFPA 13R)

S13D (not shown) = Buildings equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.3 (NFPA 13D)

Allowable Stories

Provides base (non-sprinklered) & increased # of stories

IBC 2018 Table 504.4


		Т	YPE C	F CO	NSTRU	OITO	1		50	
OCCUPANCY CLASSIFICATION	SEE FOOTNOTES	TYPE I		TYPE II		TYF	PE III	TYPE IV	TYF	PEV
	SEE FOOTNOTES	Α	В	Α	В	Α	В	НТ	Α	В
A-2	NS	UL	11	3	2	3	2	3	2	1
A-2	S	UL	12	4	3	4	3	4	3	2
A 2	NS	UL	11	3	2	3	2	3	2	1
A-3	S	UL	12	4	3	4	3	4	3	2
	NS	UL	11	5	3	5	3	5	3	2
В	S	UL	12	6	4	6	4	6	4	3
	NS ^{d, h}	UL	11	4	4 4	4	4	4	3	2
R-1	S13R	4	4	4		4	4	4	4	3
	S	Ш	12	5	5	5	5	5	4	3
	NSd, h	UL	11	4					3	2
R-2	S13R	4	4	4	4	4	4	4	4	3
* F C L C	S	UL	12	5	5	5	5	5	4	3
S 1	NS	UL	11	4	2	3	2	4	3	1
S-1	S	UL	12	5	3	4	3	5	4	2

Allowable Story Area

IBC 2018 Table 506.2

Floor Area Increase

Buildings equipped throughout with an NFPA 13 sprinkler system can be increased 300% (single story buildings) or 200% (multi-story buildings) over nonsprinklered conditions



Allowable Story Area

Provides base (non-sprinklered) & increased areas

IBC 2018 Table 506.2

TABLE 506.2°, b

ALLOWABLE AREA FACTOR (A, = NS, S1, S13R, or SM, as applicable) IN SQUARE FEET

OCCUPANCY CLASSIFICATION SEE FOOT		TYPE OF CONSTRUCTION											
	SEE FOOTNOTES	TYPEI		TYF	TYPE II		TYPE III		TYPE V				
		Α	В	Α	В	Α	В	HT	A	В			
	NS ^{d,h}	UL	UL	24,000	16,000	24,000	16,000	20,500	12,000	7,000			
D 1	S13R		OL			24,000	10,000			7,000			
R-1	S1	UL	UL	96,000	64,000	96,000	64,000	82,000	48,000	28,000			
1	SM	UL	UL	72,000	48,000	72,000	48,000	61,500	36,000	21,000			

**Can still increase these areas by the Frontage Factor of Section 506.3

NS = Buildings not equipped throughout with an automatic sprinkler system

S1 = Buildings a maximum of one story above grade plane equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.1 (NFPA 13)

SM = Buildings two or more stories above grade plane equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.1 (NFPA 13)


S13R = Buildings equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.2 (NFPA 13R)

Allowable Story Area

IBC 506.3

Area Frontage Increase

Buildings with minimum levels of open frontage can add **up to 75**% of allowable nonsprinklered area to total floor area



IBC Building Size Limits

IBC Chapter 5

Residential (R1, R2 & R4) Occupancies: Type IIIA Construction

Sprinklers Allowable Limit	NS	NFPA 13R	NFPA 13	Frontage Increase**
Stories	4	4	5	5
Height (ft)	65	60	85	85
Story Area (ft ²)	24k	24k	72k	90k
Total Building Area* (ft ²)	72k	72k	216k	270k

^{*} Assuming max stories built

^{**} Maximum allowable frontage increase

Allowable Building Size

2018 IBC Chapter 5

Residential (R1, R2 & R4) Occupancies with NFPA 13 Sprinkler System

Construction Type Allowable Limit	IIIA	IIIB	IV (HT)	VA	VB
Stories	5	5	5	4	3
Height (ft)	85	75	85	70	60
Story Area* (ft ²)	90k	60k	76.9k	45k	26.3k
2 story: Total Bldg Area (ft²)	180k	120k	153.8k	90k	52.5k
3+ story: Total Bldg Area (ft²)	270k	180k	230.6k	135k	78.8k

^{*}Assumes full frontage increase

Allowable Building Size

IBC Chapter 5

Business (B) Occupancies with NFPA 13 Sprinkler System

Construction Type Allowable Limit	IIIA	IIIB	IV (HT)	VA	VB
Stories	6	4	6	4	3
Height (ft)	85	75	85	70	60
Story Area* (ft ²)	106.9k	71.3k	135k	67.5k	33.8k
2 story: Total Bldg Area (ft²)	213.8k	142.5k	270k	135k	67.5k
3+ story: Total Bldg Area (ft²)	320.6k	213.8k	405k	202.5k	101.3k

^{*}Assumes full frontage increase

Building Configuration Options

Many buildings utilize a higher construction type than necessary due to traditional practice. This can have an impact on fire ratings, materials and ultimately cost.



Rooftop Decks

IBC 503.1

Many mixed use buildings, especially apartment buildings, are implementing occupiable roof top decks, either for individual use or as a gathering space

Historically, code didn't offer much except for basic exit provisions but several design routes have been used, plus new guidance in 2018.

Typically these spaces do not have a roof and therefore aren't classified as stories per the definition of a story (IBC 202).



Special Provisions

IBC 510

Construction Types

IBC 602.1 requires that each building be classified in one of five construction types.

IBC 510 contains special provisions that in some cases, allow multiple construction types in the same building or multiple "buildings" stacked on top of each other



Photo: Arden Photography

Special Provisions

IBC 510.2

Horizontal Building Separation

Often called *Podium provision*:

Considered separate buildings above and below for purposes of area calculations if:

- » Overall height in feet is still limited to min of either building
- » 3hr rated horizontal assembly
- » Building below is Type 1A with sprinklers


Occupancy restrictions above and below




Special Provisions

Horizontal building separation

IBC 510.2




5 story Type III Building



5 story Type III Building on top of a Type IA Podium

Increases allowable stories... not allowable building height



2015 & 2018 IBC allow multiple podium stories above grade



Wood Mid-Rise Construction





Allowable Building Size

Heights and areas calculator – free tool

http://www.woodworks.org /design-and-tools/designtools/online-calculators/

Handles Separated & Nonseparated Occupancies (Check "both")







> QUESTIONS?

This concludes The American
Institute of Architects Continuing
Education Systems Course

Warren Hamrick

APA – The Engineered Wood Association

Warren.Hamrick@APAWood.org

Jessica Scarlett

WoodWorks - Wood Products Council

Jessica.Scarlett@Woodworks.org

Copyright Materials

This presentation is protected by US and International Copyright laws.
Reproduction, distribution, display and use of the presentation without written permission of the speaker is prohibited.

© The Wood Products Council 2022

Disclaimer: The information in this presentation, including, without limitation, references to information contained in other publications or made available by other sources (collectively "information") should not be used or relied upon for any application without competent professional examination and verification of its accuracy, suitability, code compliance and applicability by a licensed engineer, architect or other professional. Neither the Wood Products Council nor its employees, consultants, nor any other individuals or entities who contributed to the information make any warranty, representative or guarantee, expressed or implied, that the information is suitable for any general or particular use, that it is compliant with applicable law, codes or ordinances, or that it is free from infringement of any patent(s), nor do they assume any legal liability or responsibility for the use, application of and/or reference to the information. Anyone making use of the information in any manner assumes all liability arising from such use.