Mass Timber Multi-Family: Studies in Carbon, Cost, and Constructability

Credits: 1.0 AIA/CES HSW LUs, 1.0 PHD credit, 0.10 ICC credit

MASS TIMBER+

OFFSITE CONSTRUCTION CONFERENCE

PRODUCED BY









Meet the Team











WoodWorks | The Wood Products Council is a registered provider of AIA-approved continuing education under Provider Number G516. All registered AIA CES Providers must comply with the AIA Standards for Continuing Education Programs. Any questions or concerns about this provider or this learning program may be sent to AIA CES (cessupport@aia.org or (800) AIA 3837, Option 3).

This learning program is registered with AIA CES for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product.

AIA continuing education credit has been reviewed and approved by AIA CES. Learners must complete the entire learning program to receive continuing education credit. AIA continuing education Learning Units earned upon completion of this course will be reported to AIA CES for AIA members. Certificates of Completion for both AIA members and non-AIA members are available upon request.

Questions related to specific materials, methods, and services will be addressed at the conclusion of this presentation.




Course Description

This session will look at the Three Regions Study, which took prototypical multi-family residential structures from three different U.S. cities and reimagined them in mass timber using construction types IV-A, IV-B, and IV-C. Representatives from SCB, LeMessurier, and Turner Construction will present the study's results, including comparative costs, construction conditions, and GWP. They will share implications for zoning and code adoption, demonstrating how mass timber allows for the maximization of housing units and the minimization of GWP with minimal cost implications. The presenters will share their analysis of the potential benefits and design considerations of mass timber construction at three scales, demonstrating the potential for mass timber to be more readily adopted into many different U.S. markets.

Learning Objectives


- 1. Explore construction types IV-A, IV-B, and IV-C as code-compliant pathways that allow the use of mass timber in building configurations typically built with other materials.
- 2. Understand the unique aspects of mass timber design and detailing to meet structural safety, fire resistance, and acoustical performance requirements.
- 3. Examine how the use of a mass timber structural system can reduce a building's global warming potential (GWP) as compared to more conventional construction materials.
- 4. Learn how building codes can be adapted or leveraged to promote high-density housing that optimizes environmental benefits without compromising quality or safety.


Forestry Supply Chain Analysis




North American Mass Timber


We chose forests to study in all three regions of the forests. These analyses of species, forest products industry infrastructure, certifications, ownerships and challenges examine each region's potential to play a role in the mass timber supply chain through sustainably grown wood products.





Minnesota, Wisconsin, and Michigan







Wood Innovation Grant Scope and Contributors

Minneapolis



Stick-Built

Denver



Cast-in-place concrete

Atlanta



Cast-in-place concrete








































Mass Timber in Three Regions

Comparative Life Cycle Assessment Study


Author: LeMessurier








Minneapolis



Denver



Atlanta



All analysis reflects mass timber equivalent calculations of existing cast-in-place concrete or stick-built structures. Cost, carbon, and constructability data all show significant gains even so; gains that will likely increase when actually designed for mass timber.

Minneapolis




Type IV-C

Max # of stories
Building height
Allowable area
Average area per story
Amount of unprotected timber
Primary structure

9 stories 85' 405,000 sf 45,000 sf 100% 2 hr rated

Denver




Type IV-B (IBC 2024)

Max # of stories
Building height
Allowable area
Average area per story
Amount of unprotected timber

Primary structure

12 stories 180' 648,000 sf 54,000 sf 100% ceiling 40% walls 2 hr rated

Atlanta




Type IV-A

Max # of stories
Building height
Allowable area
Average area per story
Amount of unprotected timber
Primary structure

18 stories 270' 972,000 sf 54,000 sf 0% 3 hr rated



Tall Mass Timber Code Adoptions







18,765,000 kgCO2eq

Cast-in-place concrete

> MATERIALS EMISSIONS & CARBON STORAGE 755,300 SF IBC 2021 TYPE IA

Fire protection - ceilings Fire protection - walls

Roofing

Exterior enclosure

Floor structure

Column & structural walls

Parking

Foundation

16%
Total reduction

GWP kgCO2eq



15,680,000 kgCO2eq

Mass timber

MATERIALS EMISSIONS & CARBON STORAGE 755,300 SF IBC 2021 TYPE IV



METHODOLOGY HERE: OLIFANT.ORG



Atlanta case study
IBC 2021 TYPE IV-A



18,765,000 kgCO2eq

Cast-in-place concrete

MATERIALS EMISSIONS & CARBON STORAGE 755,300 SF IBC 2021 TYPE IA Fire protection - ceilings

Fire protection - walls

Roofing

Exterior enclosure

Floor structure

16% Total reduction


GWP

kgCO2eq

Column & structural walls

Parking

Foundation



15,680,000 kgCO2eq

Mass timber

MATERIALS EMISSIONS & CARBON STORAGE


755,300 SF IBC 2021 TYPE IV



METHODOLOGY HERE: OLIFANT.ORG



Atlanta case study
IBC 2021 TYPE IV-A




+31%
increase with mass timber

3,833,000

5,036,000



Atlanta case study IBC 2021 Type IV-A



+\$37/sf (6% increase)

Cost comparison

Major cost drivers and impacts between superstructures of a cast-in-place concrete project and a mass timber project. Does not account for owner costs, such as schedule savings, time to market, etc. Costs are based on residential area only. Garage costs were excluded since they remained a constant in each scenario. **16** Stories 417,417 GSF of residential 340 Residential units






Atlanta case study IBC 2021 Type IV-A

Structural

Concrete structure \$30,139,000

Indirect costs¹ \$3,177,000





- Structural

Mass timber structure \$31,468,000

Fire protection: floor plates \$5,507,000

Fire protection: beams & columns \$3,181,000

Floor build up \$3,671,000

Transfer structure \$543,000

Exterior envelope \$509,000

Indirect costs¹ \$4,546,000

Schedule savings (\$1,750,000)


Cost comparison

Major cost drivers and impacts between superstructures of a cast-in-place concrete project and a mass timber project. Does not account for owner costs, such as schedule savings, time to market, etc. Costs are based on residential area only.

Garage costs were excluded since they remained a constant in each scenario.

16 Stories

417,417 GSF of residential 340 Residential units



METHODOLOGY HERE: OLIFANT.ORG





17,622,000 kgCO2eq

Cast-in-place concrete

MATERIALS EMISSIONS & CARBON STORAGE 758,500 SF IBC 2024 TYPE IA Fire protection - ceilings

Fire protection - walls

Roofing

Exterior enclosure

Floor structure


Column & structural walls

Parking

Foundation

22%
Total reduction

GWP kgCO2eq



13,800,000

Mass timber

MATERIALS EMISSIONS & CARBON STORAGE

758,500 SF IBC 2024 TYPE IV-B ON TYPE IA PODIUM







17,622,000 kgCO2eq

Cast-in-place concrete

> **MATERIALS EMISSIONS** & CARBON STORAGE 758,500 SF IBC 2024 TYPE IA

Fire protection - ceilings

Fire protection - walls

Roofing

Exterior enclosure

Floor structure

22% Total reduction **GWP**

kgCO2eq

Column & structural walls

Parking

Foundation



Mass timber


MATERIALS EMISSIONS & CARBON STORAGE

758,500 SF IBC 2024 TYPE IV-B ON TYPE IA PODIUM



METHODOLOGY HERE: OLIFANT.ORG





increase with mass timber

4,518,000

→

4,752,00

LEARN MORE ABOUT THE DATA AND METHODOLOGY HERE: OLIFANT.ORG





Major cost drivers and impacts between superstructures of a cast-in-place concrete project and a mass timber project. Does not account for owner costs, such as schedule savings, time to market, etc. Costs are based on residential area only.

Garage costs were excluded since they remained a constant in each scenario.

12 Stories

513,800 GSF of residential

395 Residential units





allows for more
wood exposure, less
carbon through
materials.

Structural

Concrete structure \$45,828,000

Indirect costs¹ \$4,830,000



Mass timber \$591/sf

Cost comparison

Major cost drivers and impacts between superstructures of a cast-in-place concrete project and a mass timber project. Does not account for owner costs, such as schedule savings, time to market, etc. Costs are based on residential area only.

Garage costs were excluded since they remained a constant in each scenario.

12 Stories

513,800 GSF of residential **395** Residential units

Structural

Mass timber structure \$36,009,000

Concrete \$8,969,000

Floor build up \$4,801,000

Fire protection: beams & columns \$3,364,000

Transfer structure \$2,810,000


Fire protection: floor plates \$1,201,000

Exterior envelope \$900,000

Indirect costs¹ \$5,832,000

Schedule savings (\$1,750,000)

Interior ceiling finishes (\$975,880)









MATERIALS EMISSIONS & CARBON STORAGE

165,340 SF IBC 2021 TYPE III-A ON TYPE IA PODIUM

Fire protection - ceilings

Fire protection - walls

Roofing

Exterior enclosure

Gypcrete topping

Acoustic underlayment

Floor structure

Column & structural walls

Foundation

42%
Total reduction

GWP kgCO2eq



Mass timber

MATERIALS EMISSIONS & CARBON STORAGE

165,340 SF IBC 2021 TYPE IV-C





3,154,000 kgCO2eq

Stick-built

MATERIALS EMISSIONS & CARBON STORAGE

165,340 SF IBC 2021 TYPE III-A ON TYPE IA PODIUM

Fire protection - ceilings

Fire protection - walls

Roofing

Exterior enclosure

Gypcrete topping

Acoustic underlayment

Floor structure

Column & structural walls

Foundation

42%
Total reduction

GWP kgCO2eq



1,823,000

kgCO2eq


Mass timber

MATERIALS EMISSIONS & CARBON STORAGE

165,340 SF IBC 2021 TYPE IV-C










METHODOLOGY HERE: OLIFANT.ORG



Minneapolis case study
IBC 2021 TYPE IV-C



Major cost drivers and impacts between superstructures of a cast-in-place concrete project and a mass timber project. Does not account for owner costs, such as schedule savings, time to market, etc.

6 Stories

165,340 GSF of residential

130 Residential units







Structure \$8,692,000

Indirect costs¹ \$916,000





Structural

Mass timber structure \$13,620,000

Indirect costs¹ \$1,170,000

Interior ceiling finishes (\$1,226,000)

Concrete foundation (\$700,000)

Exterior envelope (\$590,000)


Cost comparison

Major cost drivers and impacts between superstructures of a cast-in-place concrete project and a mass timber project. Does not account for owner costs, such as schedule savings, time to market, etc.

6 Stories

165,340 GSF of residential

130 Residential units







IBC 2021 TYPE III-A ON TYPE IA PODIUM



Minneapolis case study

42%
Total reduction kgCO2eq



IBC 2021 TYPE IV-C

Denver case study


22%
Total reduction kgCO2eq

Atlanta case study

16%
Total reduction kgCO2eq

IBC 2024 TYPE IA IBC 2021 TYPE IVA IBC 2021 TYPE IA IBC 2021 TYPE IVA

Minneapolis



¹ Mass timber stores more carbon than a stick-built structure



Colorado adopted IBC 2024, considerably reducing carbon and cost 22% reduction in GWP with mass timber structure 3% cost premium with mass timber²

² Cost likely to improve if building was originally designed for mass timber


Parking accounts for 29%


of total building carbon

3.5 month schedule savings




Atlanta








Type IV-C



Type IV-B (IBC 2024)



Type IV-A



7-12 story buildings Sweet Spot



Addressing Roadblocks to Timber





