



The Financial Dynamics of Designing with Mass Timber

Ricky McLain, WoodWorks
Nicholas Sills, Whirlwind Consultants



“The Wood Products Council” is a Registered Provider with The American Institute of Architects Continuing Education Systems (AIA/CES), Provider #G516.

Credit(s) earned on completion of this course will be reported to **AIA CES** for AIA members. Certificates of Completion for both AIA members and non-AIA members are available upon request.

This course is registered with **AIA CES** for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product.

Questions related to specific materials, methods, and services will be addressed at the conclusion of this presentation.



Course Description

Teams working to maximize the benefits of mass timber while managing costs require a nuanced understanding of the design, procurement, fabrication, and construction process. For example, keeping mass timber volumes to a minimum is key to cost-effectiveness, but can it be to the detriment of other systems in the building? How should connections be designed and detailed with cost in mind while factoring in manufacturing and fabrication capabilities, constructability and tolerances, and code and design requirements? What influence should transportation, material handling, and on-site logistics (including construction schedule targets) have on building layout and design? Are there key performance indicators that can be applied to projects to evaluate whether they're in an appropriate range at first glance? This webinar will explore the financial implications of crucial design decisions, equipping architects, structural engineers, contractors, and real estate developers with the practical knowhow necessary to create cost-effective, environmentally friendly, and structurally sound mass timber buildings.

Learning Objectives

1. Identify construction types within the International Building Code (IBC) where a mass timber structure is permitted.
2. Discuss the impacts of construction type on required fire-resistance ratings of structural elements, noting the impacts that these ratings have on effective member spans and resulting grids.
3. Review metrics that can be applied to mass timber designs to evaluate cost-effectiveness as a function of material, labor, and other factors.
4. Highlight effective methods of integrating MEP services in a mass timber building and discuss the relative impacts of each on cost, aesthetics, and structural layout.

Disclaimer

The costs and metrics represented in this presentation are a function of previous projects and experience. Each project must evaluate its unique goals and constraints, and manufacturers should be consulted for current and accurate cost information.

**WHAT'S THE #1
REASON THAT
MASS TIMBER IS
NOT USED?**

**Perception of
costs,
real costs,**



and expertise

What Impacts Mass Timber Costs?

Timber Volume

CLT glulam other

not all wood volume costs are equal

Timber Specs

species grade layup appearance

be careful what you “wish” for

Fabrication & Details

time complexity waste hardware tolerances

repetition, simplification and adjustability

What Impacts Mass Timber Costs?

Fire Rating
Piece Count Penetrations Crane Grid Size
Structural Loads Site Logistics Acoustics
Wood Volume Labor
Transportation Occupancy Complexity
Code Version Insurance Steel Volume
Design Complexity Visual Finish MEPF

HOW CAN WE DESIGN FOR COST EFFICIENCY?



INTRO, Cleveland, OH. Credit: Harbor Bay Real Estate Advisors

Key Early Design Decisions

What is the Single Most Important Early Design Decision on a Mass Timber Project? Is it:

Construction Type
Fire-Resistance Ratings
Member Sizes
Grids & Spans
Exposed Timber (where & how much)

MEP Layout
Acoustics
Concealed Spaces
Connections
Penetrations


The Answer is...They All Need to Be Weighed (Plus Others)

Key Early Design Decisions

One *potential* design route:

- 1. Building size & occupancy informs construction type & grid**
- 2. Construction type informs fire resistance ratings**
- 3. Grid & fire resistance ratings inform timber member sizes & MEP layout**

But that's not all...




Architects: The Miller Hull Partnership with
Eng
Con
Ph

Key Early Design Decisions

Other impactful decisions:

- **Acoustics** informs member sizes (and vice versa)
- Fire-resistance ratings inform **connections & penetrations**
- **MEP layout** informs use of concealed spaces




Miller Hull Partnership, photo: John Sta

Key Early Design Decisions

Other impactful decisions:

- **Grid informs efficient spans, MEP layout**
- **Manufacturer capabilities inform member sizes, grids & connections**
- **Lateral system informs connections, construction sequencing**


And more...




Platte Fifteen, Oz Architecture, KL&A
Engineers & Builders, Arch Angle Media

Mass Timber Costs

Typical MT Package Costs




Key Early Design Decisions



Panels are the biggest part of the biggest piece of the cost pie

Key Early Design Decisions


Where do we start?



MASS TIMBER IN THE CODE



Construction Types



Construction Types

When does the code allow mass timber to be used?

IBC defines mass timber systems in IBC Chapter 2 and notes their acceptance and manufacturing standards in IBC Chapter 23

Permitted anywhere that combustible materials and heavy timber are allowed, plus more



Construction Types

	TYPE I		TYPE II		TYPE III		TYPE IV				TYPE V	
	A	B	A	B	A	B	A	B	C	HT	A	B
Exterior Wall Material	Non-combustible		Non-combustible		FRTW		CLT (protected)		FRTW (LF, MT), CLT (protected)		Any wood	
Interior Elements	Non-combustible		Non-combustible		Any wood		Heavy Timber		Heavy Timber		Any wood	

8 Mass Timber Construction Types

Construction Types I-A, II-A, II-B


	TYPE I		TYPE II		TYPE III		TYPE IV				TYPE V	
	A	B	A	B	A	B	A	B	C	HT	A	B
Exterior Wall Material	Non-combustible		Non-combustible		FRTW		CLT (protected)		FRTW (LF, MT), CLT (protected)		Any wood	
Interior Elements	Non-combustible		Non-combustible		Any wood		Heavy Timber		Heavy Timber		Any wood	

Construction Types I-B, II-A, II-B

Where does the code allow wood to be used?

» Mass Timber Roof Construction

Wellesley College, Wellesley, MA



Wellesley College Science Complex / Skidmore, Owings & Merrill / Le Messurier / Photo Dave Burk © SOM

Construction Types III-A, III-B

Type III Construction:

- » Interior Elements (Floors, Roofs, Partitions/Shfts, Etc.)
 - » Any material permitted by code, including light frame and mass timber
- » Exterior Walls
 - » Non-combustible walls: light-gauge steel, curtainwall systems
 - » **FRTW light-frame walls**
 - » FRTW mass timber (NLT, DLT)
 - » Note: CLT not allowed

The Canyons, Portland, OR



The Canyons, Kaiser+Path, Cantena Consulting Engineers,
Photo Jeremy Bittermann

Construction Types V-A, V-B

Type V Construction:

- » Interior Elements (Floors, Roofs, Partitions/Shfts, Etc.)
 - » Any material permitted by code, including light frame and mass timber
- » Exterior Walls
 - » Non-combustible walls: light-gauge steel, curtainwall systems
 - » **Light-frame walls**
 - » Mass Timber

Star Lofts, Des Moines, IA



Image: Cutler Development

Construction Types IV-HT and IV-A, B, and C

Type IV-HT Construction:

- » Interior Elements
 - » Mass timber, non-combustible, or 1-hour FRR light frame
- » Exterior Walls
 - » Non-combustible
 - » CLT covered at exterior face with FRTW or noncombustible sheathing
 - » FRTW (light frame or mass timber)

The Soto, San Antonio, TX




The Soto, Hixon Properties, Lake|Flato, BOKA Powell, StructureCraft, Photo Erika Brown Edwards

Construction Types IV-A, B, and C

» Business Occupancy (Group B) Size Limits:

Type IV-A



18 STORIES
BUILDING HEIGHT 270'
PER STORY AREA 324,000 SF
BUILDING AREA 972,000 SF

Photos: Flor Projects

Type IV-B



Photos: ©Prakash Patel

12 STORIES
BUILDING HEIGHT 180'
PER STORY AREA 216,000 SF
BUILDING AREA 648,000 SF

Type IV-C



9 STORIES
BUILDING HEIGHT 85'
PER STORY AREA 135,000 SF
BUILDING AREA 405,000 SF

Monte French Design Studio, Photos: Jane Messinger

Construction Types IV-HT and IV-A, B, and C

Type IV-A, B, and C Construction:


- » Interior Elements
 - » Mass timber or non-combustible
 - » No light frame
- » Exterior Walls
 - » Non-combustible
 - » CLT covered at exterior face with noncombustible sheathing
 - » No light frame

Heartwood, Seattle, WA



Heartwood, Atelier Jones, DCI Engineers,
rendering Atelier Jones

Fire Design of MT



Key Early Design Decisions

Construction type influences FRR

TABLE 601
FIRE-RESISTANCE RATING REQUIREMENTS FOR BUILDING ELEMENTS (HOURS)

BUILDING ELEMENT	TYPE I		TYPE II		TYPE III		TYPE IV				TYPE V	
	A	B	A	B	A	B	A	B	C	HT	A	B
Primary structural frame ^e (see Section 202)	3 ^{a, b}	2 ^{a, b, c}	1 ^{b, c}	0 ^c	1 ^{b, c}	0	3 ^a	2 ^a	2 ^a	HT	1 ^{b, c}	0
Bearing walls												
Exterior ^{e, f}	3	2	1	0	2	2	3	2	2	2	1	0
Interior	3 ^a	2 ^a	1	0	1	0	3	2	2	1/HT ^g	1	0
Nonbearing walls and partitions					See Table 705.5							
Exterior					See Table 705.5							
Nonbearing walls and partitions					0	0	0	0	0	See		
Interior ^d	0	0	0	0	0	0	0	0	0	Section	0	0
Floor construction and associated secondary structural members (see Section 202)	2	2	1	0	1	0	2	2	2	HT	1	0
Roof construction and associated secondary structural members (see Section 202)	1 ^{b, c}	1 ^{b, c}	1 ^{b, c}	0 ^c	1 ^{b, c}	0	1 ^{1/2}	1	1	HT	1 ^{b, c}	0

Source: 2021 IBC

Key Early Design Decisions

Fire-Resistance Ratings (FRR)

- Thinner panels (i.e. 3-ply) generally difficult to achieve a 1+ hour FRR
- 5-ply CLT / 2x6 NLT & DLT panels can usually achieve a 1- or 2-hour FRR
- Construction Type | FRR | Member Size | Grid (or re-arrange that process but follow how one impacts the others)

Panel	Example Floor Span Ranges
3-ply CLT (4-1/8" thick)	Up to 12 ft
5-ply CLT (6-7/8" thick)	14 to 17 ft
7-ply CLT (9-5/8")	17 to 21 ft
2x4 NLT	Up to 12 ft
2x6 NLT	10 to 17 ft
2x8 NLT	14 to 21 ft
5" MPP	10 to 15 ft



GENERAL COST IMPACTS




INTRO, Cleveland, OH. Credit: Harbor Bay Real Estate Advisors

Volume of Material

- Ensure you are using the right units!
 - ft^3 or m^3 , not BF as there are nominal, and net board feet.
- Ratio of material to enclosed floor area
 - 0.3 - 0.8 $\text{ft}^3 / \text{ft}^2$ general ratio
 - 1 hr FRR 0.5 – 0.65 $\text{ft}^3 / \text{ft}^2$
 - 2 hr FRR 0.65 – 0.7 $\text{ft}^3 / \text{ft}^2$
 - 3 hr FRR 0.72 – 0.8 $\text{ft}^3 / \text{ft}^2$
- Floor Plate to Gravity Frame:
 - 30% - 40% skeleton to 60 - 70% floor plate
 - IE: 35% Glulam, 65% CLT

To Purlin, or Not to Purlin?

- Ratio of floor plate thickness to sqft of floor area
- There are many ways to reduce overall costs
 - Reduce floor plate thickness by:
 - Reducing grid size (shrink grid)
 - Reducing fire rating of wood (encapsulation)
 - Reducing plate span by adding purlins (add purlins)
 - 8-15 mins install per purlin
 - Install labor = ~15% costs, with 15% increase per grid for each purlin
 - Material = potential 40% material savings
 - Total costs = Materials $(.65)*(1-.4)+(.15*1.15)+(.20) = 76\%$ of cost for design without purlin, potential 24% savings.



Key Early Design Decisions

Panel volume usually 65-80% of MT package volume

Type IIIA option 1

1-hr FRR

Purlin: 5.5"x28.5"

Girder: 8.75"x33"


Column: 10.5"x10.75"

Floor panel: 5-ply

Glulam volume = 118 CF (22% of MT)

CLT volume = 430 CF (78% of MT)

Total volume = 0.73 CF / SF



Source: Fast + Epp, Timber Bay Design Tool

Type IV-HT

0-hr FRR (min sizes per IBC)

Purlin: 5.5"x24" (IBC min = 5"x10.5")

Girder: 8.75"x33" (IBC min = 5"x10.5")


Column: 10.5"x10.75" (IBC min = 6.75"x8.25")

Floor panel: 3-ply (IBC min = 4" CLT)

Glulam volume = 120 CF (32% of MT)

CLT volume = 258 CF (68% of MT)


Total volume = 0.51 CF / SF



Handling and Install

- Mins per piece install
 - Column 10 - 20
 - Beam 8 - 15
 - Brace/Frame 20 - 30
 - Panel 8 – 10
- Example: With loaded labour rates at \$150/ hr and a four person install crew the addition of one purlin would save 38% on the material + install package, and the addition of two purlins 45% based on shrinking material volume, but added labour time.
- Key is to ensure simple connections for smooth install.

Typical MT Package Costs



Framing Complexity Factors

- Mass Timber pricing based on material volume, connection complexity, scope adders.
- Subject to CNC machine specifications but generally:


Glulam

2 mins: Trim to Length	
10 mins: Simple	
15 mins: Simple + Drillings	
20 mins: Simple Knife Slots	
30 mins: Medium	
45 mins: Complex	
60 mins: Big + Complex	
90 mins: Difficult	
120 mins: Weird Stuff	

CLT

10 mins: Billet Trim	
15 mins: Edge+ Spline	
20 mins: Edge + Spline (Large)	
30 mins: Nested Squares	
45 mins: Nested Shapes	
60 mins: Awkward Shapes	
90 mins: Weird Stuff	

- CNC time charge anywhere from \$150 – 1000 / hr
- Poor production throughput may result in a company charging a higher markup for risk, difficulty, and loss of production output.
- Complexity also correlates to 3D BIM design time, likely number of issues and overall schedule. BIM time at \$60 - 175 / hr.




Glulam Beam CNC Time Samples


End connections, assumed the same on each end (x2)



PRECISION END TRIM
2 MINS




SIMPLE KNOTCH
8 MINS



PRE-ENG HANGER +
PURLIN HANGERS
15 MINS



SIMPLE KNIFE &
BEARING
20 MINS



CONCEALED BEARING
25 MINS



KNIFE SLOT + TIGHT FIT
PINS ARRAY
25 MINS

General scale of CNC framing time assuming Hundegger k2 style machine.

- There are key tooling limitations for slot depths, that greatly affect process time to understand some framing supplier.

2 mins: Trim to Length

10 mins: Simple

15 mins: Simple + Drillings

20 mins: Simple Knife Slots

30 mins: Medium

45 mins: Complex

60 mins: Big + Complex

90 mins: Difficult

120 mins: Weird Stuff

CLT CNC Time Samples




BILLET TRIM
10 MINS




EDGE + SPLINE
15-20 MINS



NESTED SQUARES
30 MINS



NESTED SHAPES
45 MINS



AWKWARD SHAPES
60 MINS



WEIRD STUFF
90+ MINS

General scale of CNC framing time assuming Hundegger PBA style machine.

- There are key tooling limitations for many tool heads and specific machines. Each supplier will vary +/- 20%
- Manufacture controls how nesting will occur.

10 mins: Billet Trim

15 mins: Edge+ Spline

20 mins: Edge + Spline (Large)

30 mins: Nested Squares

45 mins: Nested Shapes

60 mins: Awkward Shapes


90 mins: Weird Stuff

Cost & Schedule Savings

- Minimized site labor – Crew of 3-8 for install typical
- Scheduled overhead costs reduced (4 months to 2 months)
- Early occupancy
 - Reduced Insurance
 - Reduced Financing fees
 - Time value for occupancy


= Total potential savings

* Ensure other trades are prepared to capitalize on schedule and ensure time savings are holistically understood and executed upon



Acoustics

- Potentially governing factor for building height
 - Can add significant material volumes to expensive cladding.
 - Can push building beyond regional building allowances.
- Potentially governing factor for foundation design
 - Dead load of concrete topping can be significant in both member sizing and foundation design sizes.
 - Topping slabs can be double used for diaphragm / composite systems, likely has construction schedule implications.
- Potentially governing factor for fire
 - Acoustics should be considered as part of fire resistance rating system; smoke penetration, and thermal transfers.



Penetrations

- Pre-coordinate
 - Bets done by Architect or GC, must be in BIM scope
 - Supply 3D model of penetrations to Engineer and MT supplier
- Each hole is usually not too hard to cut if less than 8" deep
- Rule of thumb, 4 penetrations per panel is a good target
 - Roughly 2 mins per hole
 - Think of implications for many holes to CNC time.
 - Target holes under 6" diameter.



A photograph showing the interior of a modern wooden house. The walls and ceiling are made of light-colored cross-laminated timber (CLT) panels. Large windows provide ample natural light and views of the surrounding landscape. In the foreground, a kitchen area is visible with light-colored cabinetry and a stainless steel oven. The floor is made of light-colored wood planks.

Finished Surfaces

- Potentially governing for acoustics
 - Exposed vs. concealed
 - Estimated 50% increase in acoustic system costs for exposed underside of CLT
- Potentially governing for fire
 - Exposed vs. concealed
 - Each sheet of $\frac{1}{2}$ " Type X = 30 mins FRR
- Coatings: when and where?
 - Top side for moisture protection
 - Edges for moisture and checking
 - Bottom side for finished surface? How does this work during transport damages and course of construction?

Effective Design Rules of Thumb

- **Visuals**
 - Is the mass timber exposed or not?
 - Dictates large part of fire strategy
 - Dictates large part of acoustic system
- **Acoustics**
 - Top or bottom side? Dry or wet system?
- **Grid size**
 - Smaller can save material, or rectangular and remove perimeter beams and provide great options
- **Connection complexity**
 - Minimize fasteners, simple cut outs, fire protected, wood to wood when possible
- **Install sequencing**
 - Plan crane positions, and truck load arrivals of material sequenced to job site with installer
 - Coordinate during “Offered for Approval” drawing review with MT supplier



Sample Synchronized Relationships

- Visual
 - Acoustics
 - Fire → Dead load → Member sizes → Foundation sizes
- MEP strategy → Purlins
 - Grid size → Panel thickness
 - Envelop & ceiling heights → Acoustics
- Acoustics → Concrete topping → Dead load
 - Fire Performance → Panel Thickness
 - Foundation sizes



Complex set of interactions, but which are the best to focus on?

MASS TIMBER DESIGN CORRELATION MATRIX

		BASE SYSTEM DECISION						
AFFECTED SYSTEMS RELATIONSHIPS	Fire Strategy	Purlins	Grid size	Visual Exposure	MEP	Acoustic System	Foundation Design	
	Fire Strategy	X	3	3	5	2	4	0
	Purlins	3	X	4	0	5	0	0
	Grid Size	3	2	X	1	2	0	3
	Visual Exposure	5	0	1	X	4	5	0
	MEP	2	5	2	4	X	2	0
	Acoustic System	4	0	0	5	2	X	0
	Foundation Design	0	2	3	0	0	0	X
	Panel Thickness	4	5	4	4	0	2	1
	Concrete Topping	2	0	1	0	1	4	5
IMPACTS ONLY	Building Height	4	4	3	1	2	3	1
	Structural Size	4	5	5	4	2	1	3
Overall Impact:		3.1	2.6	2.6	2.4	2.0	2.1	1.3

Structural Grid



Uni-directional beams



Duda | Paine Architects
Thornton Tomasetti
Photo: WoodWorks



Bi-directional beams

Powell Studio Architecture
Gutherman Structural
Photo: WoodWorks



Stacked purlins on girders

Handel Architects
StructureCraft
Photo: StructureCraft



Double beams

Monte French Design Studio
H+O Structural Engineers
Photo Jane Messinger

Structural Grid


Member Sizes

- Impact of FRR on Sizing
- Impact of Sizing on Efficient Spans
- Consider connections – can drive member sizing

0 HR FRR: Consider 3-ply Panel

- Efficient Spans of 10-12 ft
- Grids of 20x20 (1 purlin) to 30x30 (2 purlins) may be efficient

Platte Fifteen, Denver, CO
30x30 Grid, 2 purlins per bay
3-ply CLT
Image: JC Buck



Structural Grid

Member Sizes

- Impact of FRR on Sizing
- Impact of Sizing on Efficient Spans
- Consider connections – can drive member sizing

1 or 2 HR FRR: Likely 5-ply Panel

- Efficient spans of 14-17 ft
- Grids of 15x30 (no purlins) to 30x30 (1 purlin) may be efficient

First Tech Credit Union, Hillsboro, OR

12x32 Grid, One-Way Beams
5-ply (5.5") CLT
Image: Swinerton



Structural Grid

Member Sizes

- Impact of FRR on Sizing
- Impact of Sizing on Efficient Spans
- Consider connections – can drive member sizing

1 or 2 HR FRR: Likely 5-ply Panel

- Efficient spans of 14-17 ft
- Grids of 15x30 (no purlins) to 30x30 (1 purlin) may be efficient





Clay Creative, Portland, OR
30x30 Grid, 1 purlin per bay
2x6 NLT
Image: Mackenzie



MEP Layout & Integration




MEP Layout & Integration



MEP Layout & Integration

Smaller grid bays at central core



Main MEP trunk lines around core
Smaller branches in exterior bays

What Impacts Mass Timber Costs?

Fire Rating
Piece Count Penetrations Crane Grid Size
Structural Loads Site Logistics Acoustics
Wood Volume Labor
Transportation Occupancy Complexity
Code Version Insurance Steel Volume
Design Complexity Visual Finish MEPF

Questions?

Nicholas Sills

Whirlwind Consultants

250.551.2735

nsills@whirlwindconsultants.com

Ricky McLain, PE, SE

WoodWorks

(802)498-3310

Ricky.mclain@woodworks.org

901 East Sixth, Thoughtbarn-Delineate Studio,
Leap!Structures, photo Casey Dunn



Copyright Materials

This presentation is protected by US
and International Copyright laws.

Reproduction, distribution, display and use of
the presentation without written permission
of the speaker is prohibited.

© The Wood Products Council 2024

Funding provided in part by the Softwood Lumber Board

Disclaimer: The information in this presentation, including, without limitation, references to information contained in other publications or made available by other sources (collectively “information”) should not be used or relied upon for any application without competent professional examination and verification of its accuracy, suitability, code compliance and applicability by a licensed engineer, architect or other professional. Neither the Wood Products Council nor its employees, consultants, nor any other individuals or entities who contributed to the information make any warranty, representative or guarantee, expressed or implied, that the information is suitable for any general or particular use, that it is compliant with applicable law, codes or ordinances, or that it is free from infringement of any patent(s), nor do they assume any legal liability or responsibility for the use, application of and/or reference to the information. Anyone making use of the information in any manner assumes all liability arising from such use.