

# Early Design Decisions: Priming Mass Timber Projects for Success

August 22, 2023

Presented by  
**Jessica Scarlett, EIT**  
WoodWorks

Apex Plaza / Courtesy William McDonough + Partner



“The Wood Products Council” is a Registered Provider with The American Institute of Architects Continuing Education Systems (AIA/CES), Provider #G516.

Credit(s) earned on completion of this course will be reported to **AIA CES** for AIA members. Certificates of Completion for both AIA members and non-AIA members are available upon request.

This course is registered with **AIA CES** for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product.

---

Questions related to specific materials, methods, and services will be addressed at the conclusion of this presentation.



# Course Description

---

Mass timber is a unique, non-commodity building material and, to lay the groundwork for success, certain critical decisions must be made as early as possible. These decisions can have a big impact on cost and can either increase or limit opportunities later in design. There are many cases of project teams that want to realize the full benefits of mass timber, but, because they base their designs on traditional building practices instead of optimizing them for mass timber, end up with avoidable price premiums. This presentation will walk through early project decisions and design steps, focusing on how to optimize projects for mass timber and how one early decision can influence others. Topics will include construction types, fire ratings, column grids and beam/panel spans, acoustics and MEP integration. Completed mass timber projects will be used to illustrate the variety of viable options when navigating these key decisions.

# Learning Objectives


---

1. Identify construction types within the International Building Code where a mass timber structure is permitted.
2. Discuss the impacts of construction type on required fire-resistance ratings of structural elements, noting the impacts that these ratings have on effective member spans and resulting grids.
3. Review code-compliance requirements for acoustics and primary frame connections, and provide solutions for meeting these requirements with tested mass timber assemblies.
4. Highlight effective methods of integrating MEP services in a mass timber building and discuss the relative impacts of each on cost, aesthetics, occupant comfort and future tenant renovations.



# Current State of Mass Timber Projects

As of March 2023, in the US, **1,753** multi-family, commercial, or institutional projects have been constructed with, or are in design with, mass timber.



# Key Early Design Decisions

**What is the Single Most Important Early Design Decision on a Mass Timber Project? Is it:**

**Construction Type  
Fire-Resistance Ratings  
Member Sizes  
Grids & Spans  
Exposed Timber (where & how much)**

**MEP Layout  
Acoustics  
Concealed Spaces  
Connections  
Penetrations**

**The Answer is...They All Need to Be Weighed (Plus Others)**

# Key Early Design Decisions

## Early = Efficient

Realize Efficiency in:

- Cost reduction
- Material use (optimize fiber use, minimize waste)
- Construction speed
- Trade coordination
- Minimize RFIs

Commit to a mass timber design from the start




# Key Early Design Decisions

One *potential* design route:

1. Building size & occupancy informs construction type & grid
2. Construction type informs fire resistance ratings
3. Grid & fire resistance ratings inform timber member sizes & MEP layout

But that's not all...



Architects: The Miller Hull Partnership with  
Eng  
Con  
Ph



# Key Early Design Decisions

Other impactful decisions:

- **Grid** informs efficient spans, MEP layout
- **Manufacturer capabilities** inform member sizes, grids & connections
- **Lateral system** informs connections, construction sequencing

And more...



Platte Fifteen, Oz Architecture, KL&A  
Engineers & Builders, Arch Angle Media

# Key Early Design Decisions

Other impactful decisions:


- **Acoustics** informs member sizes (and vice versa)
- Fire-resistance ratings inform **connections & penetrations**
- **MEP layout** informs use of concealed spaces



Miller Hull Partnership, photo: John Sta

# Key Early Design Decisions

Where do we start?



# Key Early Design Decisions

## Construction Type – Primarily based on building size & occupancy

	Construction Type (All Sprinklered Values)							
	IV-A	IV-B	IV-C	IV-HT	III-A	III-B	V-A	V-B
Occupancies	Allowable Building Height above Grade Plane, Feet (IBC Table 504.3)							
A, B, R	270	180	85	85	85	85	70	60
	Allowable Number of Stories above Grade Plane (IBC Table 505.4)							
A-2, A-3, A-4	18	12	6	4	4	3	3	2
B	18	12	9	6	6	4	4	3
R-2	18	12	8	5	5	5	4	3
	Allowable Area Factor (At) for SM, Feet <sup>2</sup> (IBC Table 506.2)							
A-2, A-3, A-4	135,000	90,000	56,250	45,000	42,000	28,500	34,500	18,000
B	324,000	216,000	135,000	108,000	85,500	57,000	54,000	27,000
R-2	184,500	123,000	76,875	61,500	72,000	48,000	36,000	21,000



# Key Early Design Decisions

## Construction Type – Primarily based on building size & occupancy

	Construction Type (All Sprinklered Values)							
	IV-A	IV-B	IV-C	IV-HT	III-A	III-B	V-A	V-B
Occupancies	Allowable Building Height above Grade Plane, Feet (IBC Table 504.3)							
A, B, R	270	180	85	85	85	85	70	60
<b>For low- to mid-rise mass timber buildings, there may be multiple options for construction type. There are pros and cons of each, don't assume that one type is always best.</b>								
R-2	18	12	8	5	5	5	4	3
	Allowable Area Factor (At) for SM, Feet <sup>2</sup> (IBC Table 506.2)							
A-2, A-3, A-4	135,000	90,000	56,250	45,000	42,000	28,500	34,500	18,000
B	324,000	216,000	135,000	108,000	85,500	57,000	54,000	27,000
R-2	184,500	123,000	76,875	61,500	72,000	48,000	36,000	21,000

# Key Early Design Decisions


## Fire-Resistance Ratings

- Driven primarily by construction type
- Rating achieved through timber alone or non-com protection required?

TABLE 601  
FIRE-RESISTANCE RATING REQUIREMENTS FOR BUILDING ELEMENTS (HOURS)

BUILDING ELEMENT	TYPE I		TYPE II		TYPE III		TYPE IV				TYPE V	
	A	B	A	B	A	B	A	B	C	HT	A	B
Primary structural frame <sup>f</sup> (see Section 202)	3 <sup>a, b</sup>	2 <sup>a, b, c</sup>	1 <sup>b, c</sup>	0 <sup>c</sup>	1 <sup>b, c</sup>	0	3 <sup>a</sup>	2 <sup>a</sup>	2 <sup>a</sup>	HT	1 <sup>b, c</sup>	0
Bearing walls												
Exterior <sup>a, f</sup>	3	2	1	0	2	2	3	2	2	2	1	0
Interior	3 <sup>a</sup>	2 <sup>a</sup>	1	0	1	0	3	2	2	1/HT <sup>g</sup>	1	0
Nonbearing walls and partitions Exterior					See Table 705.5							
Nonbearing walls and partitions Interior <sup>d</sup>	0	0	0	0	0	0	0	0	0	See Section 2304.11.2	0	0
Floor construction and associated secondary structural members (see Section 202)	2	2	1	0	1	0	2	2	2	HT	1	0
Roof construction and associated secondary structural members (see Section 202)	1 <sup>1/2, b</sup>	1 <sup>b, c</sup>	1 <sup>b, c</sup>	0 <sup>c</sup>	1 <sup>b, c</sup>	0	1 <sup>1/2</sup>	1	1	HT	1 <sup>b, c</sup>	0

# Construction Types



# Construction Types

## When does the code allow mass timber to be used?

IBC defines mass timber systems in IBC Chapter 2 and notes their acceptance and manufacturing standards in IBC Chapter 23

Permitted anywhere that combustible materials and heavy timber are allowed, plus more





# Construction Types

**Where does the code allow MT to be used?**

- Type IB & II: Roof Decking



Photo Credit: DeStafano & Chamberlain, Inc, Robert Benson Photography



Image: StructureCraft Builders

# Construction Types

**Where does the code allow MT to be used?**

- Type III: Interior elements (floors, roofs, partitions/shafts) and exterior walls if FRT



ICE Block I, RMW Architecture & Interiors, Buehler Engineering, Bernard André Photography

# Construction Types

## Where does the code allow MT to be used?

- Type V: All interior elements, roofs & exterior walls



Image: Christian Columbres Photography



# Construction Types

## Where does the code allow MT to be used?

- Type IV: Any exposed interior elements & roofs, must meet min. sizes; exterior walls if CLT or FRT. Concealed space limitations (varies by code version)



Image: Perkins + Will




# Construction Types

**Type IV construction permits exposed heavy/mass timber elements of min. sizes.**

Framing		Solid Sawn (nominal)	Glulam (actual)	SCL (actual)
Floor	Columns	8 x 8	$6\frac{3}{4} \times 8\frac{1}{4}$	$7 \times 7\frac{1}{2}$
	Beams	6 x 10	$5 \times 10\frac{1}{2}$	$5\frac{1}{4} \times 9\frac{1}{2}$
Roof	Columns	6 x 8	$5 \times 8\frac{1}{4}$	$5\frac{1}{4} \times 7\frac{1}{2}$
	Beams*	4 x 6	$3 \times 6\frac{7}{8}$	$3\frac{1}{2} \times 5\frac{1}{2}$

**Minimum Width by Depth in Inches**  
**See IBC 2018 2304.11 or IBC 2015 602.4 for Details**


\*3" nominal width allowed where sprinklered




# Construction Types

## Type IV concealed spaces


Until 2021 IBC, Type IV-HT provisions prohibited concealed spaces




PERMITTED INSTALLATION



PROHIBITED INSTALLATION




PROHIBITED INSTALLATION



PROHIBITED INSTALLATION

# Construction Types

## Concealed spaces solutions paper



Richard McLean, PE, SE  
Senior Technical Director – Tall Wood  
WoodWorks – Wood Products Council


### Concealed Spaces in Mass Timber and Heavy Timber Structures

Concealed spaces, such as those created by a dropped ceiling in a floor/ceiling assembly or by a stud wall assembly, have unique requirements in the International Building Code (IBC) to address the potential of fire spread in non-visible areas of a building. Section 718 of the 2018 IBC includes prescriptive requirements for protection and/or compartmentalization of concealed spaces through the use of draft stopping, fire blocking, sprinklers and other means. For information on these requirements, see the WoodWorks Q&A, *Are sprinklers required in concealed spaces such as floor and roof cavities in multi-family wood-frame buildings?*<sup>1</sup>


For mass timber building elements, the choice of construction type can have a significant impact on concealed space requirements. Because mass timber products such as cross-laminated timber (CLT) are prescriptively recognized for Type IV construction, there is a common misperception that exposed mass timber building elements cannot be used or exposed in other construction types. This is not the case.

In addition to Type IV buildings, structural mass timber elements—including CLT, glue-laminated timber (glulam), nail-laminated timber (NLT), structural composite lumber (SCL), and tongue-and-groove (T&G) decking—can be utilized and exposed in the following construction types, whether or not a fire-resistance rating is required:

- **Type III** – Floors, roofs and interior walls may be any material permitted by code, including mass timber; exterior walls are required to be noncombustible or fire retardant-treated wood.
- **Type V** – Floors, roofs, interior walls and exterior walls (i.e., the entire structure) may be constructed of mass timber.
- **Types I and II** – Mass timber may be used in select circumstances such as roof construction—including the primary frame in the 2021 IBC—in Types I-B, II-A or II-B; exterior columns and arches when 20 feet or more of horizontal separation is provided; and balconies, canopies and similar projections.



INTRO: Cleveland | Cleveland, Ohio  
Harbor Bay Real Estate Advisors  
HPA Architecture



[https://www.woodworks.org/wp-content/uploads/wood\\_solution\\_paper-Concealed\\_Spaces\\_Timber\\_Structures.pdf](https://www.woodworks.org/wp-content/uploads/wood_solution_paper-Concealed_Spaces_Timber_Structures.pdf)


# Construction Types

## Type IV concealed space options within 2021 IBC

### Option 1:

Sprinklers in concealed spaces

Dropped ceiling




# Construction Types

## Type IV concealed space options within 2021 IBC

### Option 2:

Noncombustible insulation

Dropped ceiling




# Construction Types

## Type IV concealed space options within 2021 IBC

### Option 3:

5/8" Type X gypsum on all mass timber surfaces within concealed space




Dropped ceiling






# Construction Types

New Options in 2021 IBC  
Allowable mass timber building  
size for group B occupancy with  
NFPA 13 Sprinkler



# Fire Design of MT





# Key Early Design Decisions

Construction type influences FRR

**TABLE 601**  
**FIRE-RESISTANCE RATING REQUIREMENTS FOR BUILDING ELEMENTS (HOURS)**

BUILDING ELEMENT	TYPE I		TYPE II		TYPE III		TYPE IV				TYPE V	
	A	B	A	B	A	B	A	B	C	HT	A	B
Primary structural frame <sup>f</sup> (see Section 202)	3 <sup>a, b</sup>	2 <sup>a, b, c</sup>	1 <sup>b, c</sup>	0 <sup>c</sup>	1 <sup>b, c</sup>	0	3 <sup>a</sup>	2 <sup>a</sup>	2 <sup>a</sup>	HT	1 <sup>b, c</sup>	0
Bearing walls												
Exterior <sup>e, f</sup>	3	2	1	0	2	2	3	2	2	2	1	0
Interior	3 <sup>a</sup>	2 <sup>a</sup>	1	0	1	0	3	2	2	1/HT <sup>g</sup>	1	0
Nonbearing walls and partitions Exterior					See Table 705.5							
Nonbearing walls and partitions Interior <sup>d</sup>	0	0	0	0	0	0	0	0	0	See Section 2304.11.2	0	0
Floor construction and associated secondary structural members (see Section 202)	2	2	1	0	1	0	2	2	2	HT	1	0
Roof construction and associated secondary structural members (see Section 202)	1 <sup>1/2, b</sup>	1 <sup>b, c</sup>	1 <sup>b, c</sup>	0 <sup>c</sup>	1 <sup>b, c</sup>	0	1 <sup>1/2</sup>	1	1	HT	1 <sup>b, c</sup>	0

Source: 2021 IBC

# Key Early Design Decisions

## Fire-Resistance Ratings (FRR)

- Thinner panels (i.e. 3-ply) generally difficult to achieve a 1+ hour FRR
- 5-ply CLT / 2x6 NLT & DLT panels can usually achieve a 1- or 2-hour FRR
- Construction Type | FRR | Member Size | Grid (or re-arrange that process but follow how one impacts the others)


Panel	Example Floor Span Ranges
3-ply CLT (4-1/8" thick)	Up to 12 ft
5-ply CLT (6-7/8" thick)	14 to 17 ft
7-ply CLT (9-5/8")	17 to 21 ft
2x4 NLT	Up to 12 ft
2x6 NLT	10 to 17 ft
2x8 NLT	14 to 21 ft
5" MPP	10 to 15 ft



# Key Early Design Decisions

## Which Method of Demonstrating FRR of MT is Being Used?

1. Calculations in Accordance with IBC 722 → NDS Chapter 16
2. Tests in Accordance with ASTM E119



# FRR Design of MT

Nominal char rate of 1.5"/HR is recognized in NDS. Effective char depth calculated to account for duration, structural reduction in heat-affected zone



Credit: ARUP

**Table 16.2.1A Char Depth and Effective Char Depth (for  $\beta_n = 1.5 \text{ in./hr.}$ )**

Required Fire Resistance (hr.)	Char Depth, $a_{\text{char}}$ (in.)	Effective Char Depth, $a_{\text{eff}}$ (in.)
1-Hour	1.5	1.8
1½-Hour	2.1	2.5
2-Hour	2.6	3.2

**Table 16.2.1B Effective Char Depths (for CLT with  $\beta_n = 1.5 \text{ in./hr.}$ )**


Required Fire Endurance (hr.)	Effective Char Depths, $a_{\text{char}}$ (in.)								
	lamination thicknesses, $h_{\text{lam}}$ (in.)								
	5/8	3/4	7/8	1	1-1/4	1-3/8	1-1/2	1-3/4	2
1-Hour	2.2	2.2	2.1	2.0	2.0	1.9	1.8	1.8	1.8
1½-Hour	3.4	3.2	3.1	3.0	2.9	2.8	2.8	2.8	2.6
2-Hour	4.4	4.3	4.1	4.0	3.9	3.8	3.6	3.6	3.6




# FRR Design of MT

Two structural capacity checks performed:

1. On entire cross section neglecting fire effects
2. On post-fire remaining section, with stress increases



Credit: Forest Products Laboratory



$$a_{\text{char}} = \beta_t t^{0.813}$$

Solid Sawn, Glulam, SCL

$$a_{\text{char}} = n_{\text{lam}} h_{\text{lam}} + \beta_t \left( t - (n_{\text{lam}} t_{\text{gl}}) \right)^{0.813}$$


CLT

$$a_{\text{eff}} = 1.2 a_{\text{char}}$$

Effective Char Depth

# FRR Design of MT

AWC's TR10 is a technical design guide, aids in the use of NDS  
Chapter 16 calculations



## Example 5: Exposed CLT Floor - Allowable Stress Design

Simply-supported cross-laminated timber (CLT) floor spanning  $L=18$  ft in the strong-axis direction. The design loads are  $q_{live}=80$  psf and  $q_{dead}=30$  psf including estimated self-weight of the CLT panel. Floor decking, nailed to the unexposed face of CLT panel, is spaced to restrict hot gases from venting through half-lap joints at edges of CLT panel sections. Calculate the required section dimensions for a 1-hour structural fire resistance time when subjected to an ASTM E119 fire exposure.

For the structural design of the CLT panel, calculate the maximum induced moment.

Calculate panel load (per foot of width):

$$W_{load} = (q_{dead} + q_{live}) = (30 \text{ psf} + 80 \text{ psf})(1 \text{ ft width}) = 110 \text{ plf/ft of width}$$

Calculate maximum induced moment (per foot of width):

$$M_{max} = W_{load} L^2 / 8 = (110)(18^2)/8 = 4,455 \text{ ft-lb/ft of width}$$

From PRG 320, select a 5-ply CLT floor panel made from 1-3/8 in x 3-1/2 in. lumber boards (CLT thickness of 6-7/8 inches). For CLT grade V2, tabulated properties are:

$$\text{Bending moment, } F_b S_{eff,0} = 4,675 \text{ ft-lb/ft of width} \quad (\text{PRG 320 Annex A, Table A2})$$

Calculate the allowable design moment (assuming  $C_D=1.0$ ;  $C_M=1.0$ ;  $C_t=1.0$ ;  $C_L=1.0$ )

$$M_s' = F_b(S_{eff})(C_D)(C_M)(C_t)(C_L) = 4,675 (1.0)(1.0)(1.0) = 4,675 \text{ ft-lb/ft of width} \quad (\text{NDS 10.3.1})$$

$$\text{Structural Check:} \quad M_s' \geq M_{max} \quad 4,675 \text{ ft-lb/ft} > 4,455 \text{ ft-lb/ft} \quad \checkmark$$



(note: serviceability check is not performed to simplify the design example, but should be done in typical structural design).

Source: AWC's TR10

# FRR Design of MT

## Tested FRR of Exposed MT:


- Many successful Mass Timber ASTM E119 fire tests have been completed by industry & manufacturers


 **Fire Testing Laboratory** 

**TEST REPORT** Page 1 of 53  
for  
**American Wood Council**  
222 Catootin Circle SE, Suite 201  
Leesburg, VA 20175

**Standard Methods of  
Fire Tests of Building Construction and Materials  
ASTM E 119 – 11a**


Test Report No: WP-1950  
Assignment No: K-1089  
Subject Material: Cross-Laminated Timber and Gypsum Board Wall Assembly (Load-Bearing)  
Test Date: October 4, 2012  
Report Date: October 15, 2012

Prepared by:   
Michael J. Ridzo  
Test Engineer

Reviewed by:   
Robert J. Manchetti  
Director, Laboratory Facilities and Testing Services

This results reported in this document apply to specific samples submitted for measurement.  
No responsibility is assumed for performance of any other specimens.  
This report may not be reproduced, except in full, without the written approval of the laboratory.  
The laboratory's test report in no way constitutes or implies product certification, approval or endorsement by this laboratory.

**TEST REPORT**




**REPORT NUMBER: 102891256SAT-001**  
ORIGINAL ISSUE DATE: February 27, 2017  
REVISED DATE: N/A

**EVALUATION CENTER**  
16015 Shady Falls Road  
Elmendorf, TX 78112  
Phone: (210) 635-8100  
Fax: (210) 635-8101  
www.intertek.com

**RENDERED TO**  
**Structurlam Products LP**  
2176 Government Street  
Penticton, BC V2A 8B5  
Canada

PRODUCT EVALUATED: CrossLam® CLT Un-restrained Load-Bearing Floor/Ceiling Assembly  
EVALUATION PROPERTY: Fire Resistance

**Report of Testing a CrossLam® CLT Un-restrained Load-Bearing Floor/Ceiling Assembly for compliance with the applicable requirements of the following criteria: ASTM E119-16a, Standard Test Methods for Fire Tests of Building Construction and Materials, and CAN/ULC S404, Standard Methods of Fire**

 **ARC-CARC**

Project No. 301006155  
Final Report 2012/13

**Preliminary CLT Fire Resistance Testing Report**

by  
Lindsay Osborne, M.A.Sc.  
Christian Dagenais, Eng., M.Sc.  
Scientists  
Advanced Building Systems – Serviceability and Fire Group

and  
Noureddine Bénichou, Ph.D.  
Senior Research Officer  
National Research Council of Canada – Fire Research Resource Centre

July 2012

# FRR Design of MT

## WoodWorks Inventory of Fire Tested MT Assemblies

Table 1: North American Fire Resistance Tests of Mass Timber Floor / Roof Assemblies



CLT Panel	Manufacturer	CLT Grade or Major x Minor Grade	Ceiling Protection	Panel Connection in Test	Floor Topping	Load Rating	Fire Resistance Achieved (Hours)	Source	Testing Lab
3-ply CLT (114mm 4.488 in)	Nordic	SPF 1650 Fb 1.5 EMSR x SPF #3	2 layers 1/2" Type X gypsum	Half-Lap	None	Reduced 36% Moment Capacity	1	1 (Test 1)	NRC Fire Laboratory
3-ply CLT (105mm 4.133 in)	Structurlam	SPF #1/#2 x SPF #1/#2	1 layer 5/8" Type X gypsum	Half-Lap	None	Reduced 75% Moment Capacity	1	1 (Test 5)	NRC Fire Laboratory
5-ply CLT (175mm 6.875")	Nordic	EI	None	Topside Spline	2 staggered layers of 1/2" cement boards	Loaded, See Manufacturer	2	2	NRC Fire Laboratory March 2016
5-ply CLT (175mm 6.875")	Nordic	EI	1 layer of 5/8" Type X gypsum under Z-channels and furring strips with 3 5/8" fiberglas batts	Topside Spline	2 staggered layers of 1/2" cement boards	Loaded, See Manufacturer	2	5	NRC Fire Laboratory Nov 2014
5-ply CLT (175mm 6.875")	Nordic	EI	None	Topside Spline	3/4 in. proprietary gypcrete over Maxxon acoustical mat	Reduced 50% Moment Capacity	1.5	3	UL
5-ply CLT (175mm 6.875")	Nordic	EI	1 layer 5/8" normal gypsum	Topside Spline	3/4 in. proprietary gypcrete over Maxxon acoustical mat or proprietary sound board	Reduced 50% Moment Capacity	2	4	UL
5-ply CLT (175mm 6.875")	Nordic	EI	1 layer 5/8" Type X Gyp under Resilient Channel under 7 3/8" J-Joints with 3 1/2" Mineral Wool between Joists	Half-Lap	None	Loaded, See Manufacturer	2	21	Intertek 8/24/2012
5-ply CLT (175mm 6.875")	Structurlam	EI M5 MSR 2100 x SPF #2	None	Topside Spline	1-1/2" Maxxon Cyp-Grete 2000 over Maxxon Reinforcing Mesh	Loaded, See Manufacturer	2.5	6	Intertek, 2/22/2016
5-ply CLT (175mm 6.875")	DR Johnson	VI	None	Half-Lap & Topside Spline	2" gypsum topping	Loaded, See Manufacturer	2	7	SwRI (May 2016)
5-ply CLT (175mm 6.875")	Nordic	SPF 1950 Fb MSR x SPF #3	None	Half-Lap	None	Reduced 59% Moment Capacity	1.5	1 (Test 3)	NRC Fire Laboratory
5-ply CLT (175mm 6.875")	Structurlam	SPF #1/#2 x SPF #1/#2	1 layer 5/8" Type X gypsum	Half-Lap	None	Unreduced 101% Moment Capacity	2	1 (Test 6)	NRC Fire Laboratory
7-ply CLT (245mm 9.65")	Structurlam	SPF #1/#2 x SPF #1/#2	None	Half-Lap	None	Unreduced 101% Moment Capacity	2.5	1 (Test 7)	NRC Fire Laboratory
5-ply CLT (175mm 6.875")	SmartLam	SL-V4	None	Half-Lap	nominal 1/2" plywood with 8d nails.	Loaded, See Manufacturer	2	12 (Test 4)	Western Fire Center 10/26/2016
5-ply CLT (175mm 6.875")	SmartLam	VI	None	Half-Lap	nominal 1/2" plywood with 8d nails.	Loaded, See Manufacturer	2	12 (Test 5)	Western Fire Center 10/28/2016
5-ply CLT (175mm 6.875")	DR Johnson	VI	None	Half-Lap	nominal 1/2" plywood with 8d nails.	Loaded, See Manufacturer	2	12 (Test 6)	Western Fire Center 11/01/2016
5-ply CLT (175mm 6.875")	KLIH	CV3M1	None	Half-Lap & Topside Spline	None	Loaded, See Manufacturer	1	18	SwRI



# FRR Design of MT

Method of demonstrating FRR (calculations or testing) can impact member sizing

Each has unique benefits:

- **Testing:**
  - Can result in higher FRR for some assemblies when compared to calculations (i.e. 2-hr FRR with 5-ply CLT panel).
  - Seen as more acceptable by some building officials
- **Calculations:**
  - Can provide more design flexibility
  - Allows for project span and loading specific analysis

# FRR Design of MT



## Fire-Resistive Design of Mass Timber Members

Code Applications, Construction Types and Fire Ratings

Richard McLain, PE, SE • Senior Technical Director • WoodWorks  
Scott Bleneman, PhD, PE, SE • Senior Technical Director • WoodWorks

For many years, exposed heavy timber framing elements have been permitted in U.S. buildings due to their inherent fire-resistance properties. The predictability of wood's char rate has been well-established for decades and has long been recognized in building codes and standards.

Today, one of the exciting trends in building design is the growing use of mass timber—i.e., large solid wood panel products such as cross-laminated timber (CLT) and nail-laminated timber (NLT)—for floor, wall and roof construction. Like heavy timber, mass timber products have inherent fire resistance that allows them to be left exposed and still achieve a fire-resistance rating. Because of their strength and dimensional stability, these products also offer a low-carbon alternative to steel, concrete, and masonry for many applications. It is this combination of exposed structure and strength that developers and designers across the country

are leveraging to create innovative designs with a warm yet modern aesthetic, often for projects that go beyond traditional norms of wood design.

This paper has been written to support architects and engineers exploring the use of mass timber for commercial and multi-family construction. It focuses on how to meet fire-resistance requirements in the International Building Code (IBC), including calculation and testing-based methods. Unless otherwise noted, references refer to the 2018 IBC.

### Mass Timber & Construction Type

Before demonstrating fire-resistance ratings of exposed mass timber elements, it's important to understand under what circumstances the code currently allows the use of mass timber in commercial and multi-family construction.

A building's assigned construction type is the main indicator of where and when all wood systems can be used. IBC Section 602 defines five main options (Type I through V) with all but Type IV having subcategories A and B. Types III and V permit the use of wood framing throughout much of the structure and both are used extensively for modern mass timber buildings.

**Type III** (IBC 602.3) – Timber elements can be used in floors, roofs and interior walls. Fire-retardant-treated wood (FRTW) framing is permitted in exterior walls with a fire-resistance rating of 2 hours or less.

**Type V** (IBC 602.5) – Timber elements can be used throughout the structure, including floors, roofs and both interior and exterior walls.

**Type IV** (IBC 602.4) – Commonly referred to as "Heavy Timber" construction, this option



Carbon12 | Portland, Oregon  
Kaiser Group | Path Architecture  
Munzing Structural Engineering

## Mass Timber Fire Design Resource

- Code compliance options for demonstrating FRR
- Free download at [woodworks.org](http://woodworks.org)


# Structural Grid



# Structural Grid

## Grids & Spans

- Consider Efficient Layouts
- Repetition & Scale
- Manufacturer Panel Sizing
- Transportation





# Structural Grid

## Member Sizes

- Impact of FRR on Sizing
- **Impact of Sizing on Efficient Spans**
- Consider connections – can drive member sizing

## 0 HR FRR: Consider 3-ply Panel

- Efficient Spans of 10-12 ft
- Grids of 20x20 (1 purlin) to 30x30 (2 purlins) may be efficient

Albina Yard, Portland, OR  
20x20 Grid, 1 purlin per bay  
3-ply CLT  
Image: Lever Architecture





# Structural Grid

## Member Sizes

- Impact of FRR on Sizing
- **Impact of Sizing on Efficient Spans**
- Consider connections – can drive member sizing

## 1 or 2 HR FRR: Likely 5-ply Panel



- Efficient spans of 14-17 ft
- Grids of 15x30 (no purlins) to 30x30 (1 purlin) may be efficient

Clay Creative, Portland, OR  
30x30 Grid, 1 purlin per bay  
2x6 NLT  
Image: Mackenzie



# Key Early Design Decisions

## NEW MASS TIMBER FLOOR VIBRATION DESIGN GUIDE



U.S. Mass Timber  
Floor Vibration

Design Guide



Worked office, lab  
and residential  
Examples

*Covers simple and complex  
methods for bearing wall and  
frame supported floor systems*

# Key Early Design Decisions

## Construction Type Early Decision Example



### 7-story building on health campus


- Group B occupancy, NFPA 13 sprinklers throughout
- Floor plate = 22,300 SF
- Total Building Area = 156,100 SF

### MT Construction Type Options:

- **If Building is < 85 ft**
  - 7 stories of IV-C
  - 6 stories of IIIA or IV-HT over 1 story IA podium
- **If Building is > 85 ft**
  - 7 stories of IV-B

## Key Early Design Decisions

Panel volume usually 65-80% of MT package volume



Source: Fast + Epp, Timber Bay Design Tool

### Type IIIA option 1

1-hr FRR

Purlin: 5.5"x28.5"

Girder: 8.75"x33"

Column: 10.5"x10.75"

Floor panel: 5-ply

Glulam volume = 118 CF (22% of MT)


CLT volume = 430 CF (78% of MT)

Total volume = 0.73 CF / SF



## Key Early Design Decisions

Panel volume usually 65-80% of MT package volume



Source: Fast + Epp, Timber Bay Design Tool

### Type IIIA option 2

1-hr FRR

Purlin: 5.5"x24"

Girder: 8.75"x33"

Column: 10.5"x10.75"

Floor panel: 5-ply

Glulam volume = 123 CF (22% of MT)


CLT volume = 430 CF (78% of MT)

Total volume = 0.74 CF / SF

Cost considerations: One additional beam (one additional erection pick), 2 more connections

# Key Early Design Decisions

Panel volume usually 65-80% of MT package volume



Source: Fast + Epp, Timber Bay Design Tool

## Type IV-HT

0-hr FRR (min sizes per IBC)

Purlin: 5.5"x24" (IBC min = 5"x10.5")

Girder: 8.75"x33" (IBC min = 5"x10.5")

Column: 10.5"x10.75" (IBC min = 6.75"x8.25")

Floor panel: 3-ply (IBC min = 4" CLT)


Glulam volume = 120 CF (32% of MT)

CLT volume = 258 CF (68% of MT)

Total volume = 0.51 CF / SF

## Key Early Design Decisions

Panel volume usually 65-80% of MT package volume



Source: Fast + Epp, Timber Bay Design Tool

### Type IV-C

2-hr FRR

Purlin: 8.75"x28.5"

Girder: 10.75"x33"

Column: 13.5"x21.5"

Floor panel: 5-ply


Glulam volume = 183 CF (30% of MT)

CLT volume = 430 CF (70% of MT)

Total volume = 0.82 CF / SF

# Key Early Design Decisions

## Which is the most efficient option?



Source: Fast + Epp, Timber Bay Design Tool

	Timber Volume Ratio	Podium on 1 <sup>st</sup> Floor?
IIIA – Option 1	0.73 CF / SF	Yes
IIIA – Option 2	0.74 CF / SF	Yes
IV-HT	0.51 CF / SF	Yes
IV-C	0.82 CF / SF	No

A general rule of thumb for efficient mass timber fiber volume is no higher than 0.75 CF per SF. Ratios in the 0.85 to 1.0 CF / SF range tend to become cost prohibitive




## **Key Early Design Decisions**

**Why so much focus on panel thickness?**



## Key Early Design Decisions



**Panels are the biggest part of the biggest piece of the cost pie**




**Time for questions  
and a short break!**



Apex Plaza / Courtesy William McDonough + Partner

# Connections



Credit: Structurlam



# Key Early Design Decisions

Many ways to demonstrate connection fire protection: calculations, prescriptive NC, test results, others as approved by AHJ



Photo: John Stamets



Photo: Josh Partee



Photo: Christian Columbres





Photo: Blaine Brownell

## Key Early Design Decisions

Steel hangers/hardware fully concealed within a timber-to-timber connection is a common method of fire protection



# Key Early Design Decisions

2017 Glulam Beam to Column Connection Fire Tests under standard ASTM E119 time-temperature exposure





## Key Early Design Decisions

Member to member bearing also commonly used, can avoid some/all steel hardware at connection







# Key Early Design Decisions

**2304.10.1 Connection fire resistance rating.** Fire resistance ratings in Type IV-A, IV-B, or IV-C construction shall be determined by one of the following:

1. Testing in accordance with Section 703.2 where the connection is part of the fire resistance test.
2. Engineering analysis that demonstrates that the temperature rise at any portion of the connection is limited to an average temperature rise of 250° F (139° C), and a maximum temperature rise of 325° F (181° C), for a time corresponding to the required fire resistance rating of the structural element being connected. For the purposes of this analysis, the connection includes connectors, fasteners, and portions of wood members included in the structural design of the connection.



Source: AWC's TR 10



# Key Early Design Decisions



**KL&A**  
Engineers & Builders



ARCHITECTURE  
URBAN DESIGN  
INTERIOR DESIGN

**SWINERTON**  
MASS TIMBER




## WoodWorks Index of Mass Timber Connections



## MASS TIMBER CONNECTIONS INDEX

A library of commonly used mass timber connections with designer notes and information on fire resistance, relative cost and load-carrying capacity.



# Connections

## Other connection design considerations:

- Structural capacity
- Shrinkage
- Constructability
- Aesthetics
- Cost



Credit: Alex Schreyer



# Penetrations & Firestopping



Photo: Alex Schreyer



# Penetrations & Firestopping

Construction Type Impacts FRR | FRR impacts penetration firestopping requirements

**714.1.1 Ducts and air transfer openings.** Penetrations of fire-resistance-rated walls by ducts that are not protected with *dampers* shall comply with Sections 714.3 through 714.4.3. Penetrations of *horizontal assemblies* not protected with a shaft as permitted by Section 717.6, and not required to be protected with *fire dampers* by other sections of this code, shall comply with Sections 714.5 through 714.6.2. Ducts and air transfer openings that are protected with *dampers* shall comply with Section 717.




# Penetrations & Firestopping

Option 1: MT penetration firestopping via tested products




# Penetrations & Firestopping

Most firestopping systems include combination of fire safing (eg. noncombustible materials such as mineral wool insulation) plus fire caulk



Photos: AWC/FPInnovations/Hilti





# Penetrations & Firestopping

## Inventory of Fire Tested Penetrations in MT Assemblies



**Table 3: North American Fire Tests of Penetrations and Fire Stops in CLT Assemblies**


CLT Panel	Exposed Side Protection	Penetrating Item	Penetrant Centered or Offset in Hole	Firestopping System Description	F Rating	T Rating	Stated Test Protocol	Source	Testing Lab
3-ply (78mm 3.07")	None	1.5" diameter data cable bunch	Centered	3.5 in diameter hole. Mineral wool was installed in the 1 in. annular space around the data cables to a total depth of approximately 2 – 5/64 in. The remaining 1 in. annular space from the top of the mineral wool to the top of the floor assembly was filled with Hilti FS-One Max caulking.	1 hour	0.5 hour	CANULC S115	26	Intertek March 30, 2016
3-ply (78mm 3.07")	None	2" copper pipe	Centered	4.375 in diameter hole. Pipe wrap was installed around the copper pipe to a total depth of approximately 2 – 5/64 in. The remaining 1 in. annular space starting at the top of the mineral wool to the top of the floor assembly was filled with Hilti FS-One Max caulking.	1 hour	NA.	CANULC S115	26	Intertek March 30, 2016
3-ply (78mm 3.07")	None	2.5" sched. 40 pipe	Centered	4.92 in diameter hole. Pipe wrap was installed around the schedule 40 pipe to a total depth of approximately 2 – 5/64 in. The remaining 1 in. annular space starting at the top of the pipe wrap to the top of the floor assembly was filled with Hilti FS-One Max caulking.	1 hour	NA.	CANULC S115	26	Intertek March 30, 2016
3-ply (78mm 3.07")	None	6" cast iron pipe	Centered	8.35 in diameter hole. Mineral wool was installed in the 1 in. annular space around the cast iron pipe to a total depth of approximately 2 – 5/64 in. The remaining 1 in. annular space starting at the top of the pipe wrap to the top of the floor assembly was filled with Hilti FS-One Max caulking.	1 hour	NA.	CANULC S115	26	Intertek March 30, 2016
3-ply (78mm 3.07")	None	Hilti 6 in drop in device. System No.: F-B-2049	Centered	9.01" diameter hole. Mineral wool was installed in the 1 – 1/4 in. annular space around the drop-in device to a total depth of approximately 1 – 7/64 in and the remaining 1 in. annular space from the top of the mineral wool to the top edge of the 9 – 1/64 in. hole in the CLT was filled with Hilti FS-One Max caulking.	1 hour	0.75 hour	CANULC S115	26	Intertek March 30, 2016
5-ply CLT (131mm 5.16")	None	1.5" diameter data cable bunch	Centered	3.5" diameter hole. Mineral wool was installed in the 1 in. annular space around the data cables to a total depth of approximately 4 – 5/32 in. The remaining 1 in. annular space from the top of the mineral wool to the top of the floor assembly was filled with Hilti FS-One Max caulking.	2 hours	1.5 hours	CANULC S115	26	Intertek March 30, 2016
5-ply CLT (131mm 5.16")	None	2" copper pipe	Centered	4.375 in diameter hole. Pipe wrap was installed around the copper pipe to a total depth of approximately 4 – 5/32 in. The remaining 1 in. annular space starting at the top of the mineral wool to the top of the floor assembly was filled with Hilti FS-One Max caulking.	2 hours	NA.	CANULC S115	26	Intertek March 30, 2016
5-ply CLT (131mm 5.16")	None	2.5" sched. 40 pipe	Centered	4.92 in diameter hole. Pipe wrap was installed around the schedule 40 pipe to a total depth of approximately 4 – 5/32 in. The remaining 1 in. annular space starting at the top of the pipe wrap to the top of the floor assembly was filled with Hilti FS-One Max caulking.	2 hours	0.5 hour	CANULC S115	26	Intertek March 30, 2016
5-ply CLT (131mm 5.16")	None	6" cast iron pipe	Centered	8.35 in diameter hole. Mineral wool was installed in the 1 in. annular space around the cast iron pipe to a total depth of approximately 4 – 5/32 in. The remaining 1 in. annular space starting at the top of the pipe wrap to the top of the floor assembly was filled with Hilti FS-One Max caulking.	2 hours	NA.	CANULC S115	26	Intertek March 30, 2016
5-ply CLT (131mm 5.16")	None	Hilti 6 in drop in device. System No.: F-B-2049	Centered	9.01" diameter hole. Mineral wool was installed in the 1 – 1/4 in. annular space around the drop-in device to a total depth of approximately 1 – 7/64 in and the remaining 1 in. annular space from the top of the mineral wool to the top edge of the 9 – 1/64 in. hole in the CLT was filled with Hilti FS-One Max caulking.	2 hours	1.5 hours	CANULC S115	26	Intertek March 30, 2016
5-ply (175mm 6.875")	None	1" nominal PVC pipe	Centered	4.21 in diameter with a 3/4 in plywood reducer flush with the top of the slab reducing the opening to 2.28 in. Two wraps of Hilti CP 648-E W45/1-3/4" Firestop wrap strip at two locations with a 30 gauge steel sleeve which extended from the top of the slab to 1 in below the slab. The first location was with the bottom of the wrap strip flush with the bottom of the steel sleeve and the second was with the bottom of the wrap strip 3 in. from the bottom of the slab. The void between the steel sleeve and the CLT and between the steel sleeve and pipe at the top was filled with Roxul Safe mineral wool leaving a 3/4 in deep void at the top of the assembly. Hilti FS-One Max Intumescent Firestop Sealant was applied to a depth of 3/4 in on the top of the assembly between the plywood and steel sleeve as well as the steel sleeve and pipe.	2 hours	2 hours	ASTM E814	24	QAI Laboratories March 3, 2017




# Penetrations & Firestopping

Beam penetrations:


- If FRR = 0-hr, analyze structural impact of hole diameter only
- If FRR > 0-hr, account for charred hole diameter or firestop penetration



Hole diameter



Hole diameter after 1-hr char



# MEP Layout & Integration







# MEP Layout & Integration

Set Realistic Owner Expectations About Aesthetics

- MEP fully exposed with MT structure, or limited exposure?



# MEP Layout & Integration

## Key considerations:

- Level of exposure desired
- Floor to floor, structure depth & desired head height
- Building occupancy and configuration (i.e. central core vs. double loaded corridor)
- Grid layout and beam orientations
- Need for future tenant reconfiguration
- Impact on fire & structural design: concealed spaces, penetrations




Credit: WoodWorks



# MEP Layout & Integration

Smaller grid bays at central core



Main MEP trunk lines around core


Smaller branches in exterior bays

Credit: ARUP


# MEP Layout & Integration

Smaller grid bays at central core (more head height)

- Main MEP trunk lines around core, smaller branches in exterior bays



Credit: Blaine Brownell




Credit: WoodWorks



# MEP Layout & Integration

Dropped below MT framing

- Can simplify coordination (fewer penetrations)
- Bigger impact on head height



Credit: Alex Schreyer



Credit: WoodWorks

# MEP Layout & Integration

In penetrations through MT framing

- Requires more coordination (penetrations)
- Bigger impact on structural capacity of penetrated members
- Minimal impact on head height






# MEP Layout & Integration

In chases above beams and below panels

- Fewer penetrations
- Bigger impact on head height (overall structure depth is greater)
- FRR impacts: top of beam exposure



Credit: JC Buck




Credit: KL&A Engineers & Builders

# MEP Layout & Integration

In chases above beams and below panels at Catalyst

- 30x30 grid, 5-ply CLT ribbed beam system





# MEP Layout & Integration

In gaps between MT panels


- Fewer penetrations, can allow for easier modifications later




# MEP Layout & Integration

In gaps between MT panels

- FRR impacts: generally topping slab relied on for FRR



Credit: KPFF





# MEP Layout & Integration

In gaps between MT panels

- Aesthetics: often uses ceiling panels to cover gaps



Credit: Ema Peter/MGA

# MEP Layout & Integration

- In raised access floor (RAF) above MT
- Aesthetics (minimal exposed MEP)






# MEP Layout & Integration

In raised access floor (RAF) above MT

- Impact on head height
- Concealed space code provisions



Credit: Global IFS



# MEP Layout & Integration

In topping slab above MT

- Greater need for coordination prior to slab pour
- Limitations on what can be placed (thickness of topping slab)
- No opportunity for renovations later




Credit: Alex Schreyer



# Acoustics & Sound Control




# Acoustics & Sound Control



Images: Maxxon

- Finish Floor if Applicable
- Concrete/Gypsum Topping
- Acoustical Mat Product
- CLT Panel
- No direct applied or hung ceiling



# Acoustics & Sound Control

Code requirements only address residential occupancies:


For unit to unit or unit to public or service areas:

**Min. STC of 50 (45 if field tested):**

- Walls, Partitions, and Floor/Ceiling Assemblies

**Min. IIC of 50 (45 if field tested) for:**


- Floor/Ceiling Assemblies





# Acoustics & Sound Control

MT: Structure Often is Finish



Photos: Baumberger Studio/PATH Architecture/Marcus Kauffman | Architect: Kaiser + PATH

# Acoustics & Sound Control

But by Itself, Not Adequate for Acoustics



# Acoustics & Sound Control

**TABLE 1:**  
**Examples of Acoustically-Tested Mass Timber Panels**

Mass Timber Panel	Thickness	STC Rating	IIC Rating
3-ply CLT wall <sup>4</sup>	3.07"	33	N/A
5-ply CLT wall <sup>4</sup>	6.875"	38	N/A
5-ply CLT floor <sup>5</sup>	5.1875"	39	22
5-ply CLT floor <sup>4</sup>	6.875"	41	25
7-ply CLT floor <sup>4</sup>	9.65"	44	30
2x4 NLT wall <sup>6</sup>	3-1/2" bare NLT 4-1/4" with 3/4" plywood	24 bare NLT 29 with 3/4" plywood	N/A
2x6 NLT wall <sup>6</sup>	5-1/2" bare NLT 6-1/4" with 3/4" plywood	22 bare NLT 31 with 3/4" plywood	N/A
2x6 NLT floor + 1/2" plywood <sup>2</sup>	6" with 1/2" plywood	34	33

Source: Inventory of Acoustically-Tested Mass Timber Assemblies, WoodWorks<sup>7</sup>



# Acoustics & Sound Control

**Regardless of the structural materials used in a wall or floor ceiling assembly, there are 3 effective methods of improving acoustical performance:**

1. Add mass
2. Add noise barriers
3. Add decouplers





Image credit: Christian Columbres



# Acoustics & Sound Control

**What does this look like in typical wood-frame construction:**

1. Add mass
2. Add noise barriers
3. Add decouplers



---

STC 62


---

# Acoustics & Sound Control

**Mass timber has relatively low “mass”**

**Recall the three ways to increase acoustical performance:**

1. Add mass
2. ~~Add noise barriers~~
3. Add decouplers



Credit: Christian Columbres

# Acoustics & Sound Control



Concrete Slab:

6" Thick

80 PSF

STC 53



CLT Slab:

6-7/8" Thick

18 PSF

STC 41



# Acoustics & Sound Control

Acoustical floor underlayments



Photo: AcoustiTECH<sup>10</sup>




Photo: Kinetics Noise Control, Inc.,<sup>11</sup>



Photo: Maxxon Corporation




Photo: Pliteq Inc.,<sup>12</sup>



# Acoustics & Sound Control

## Common mass timber floor assembly:

- Finish floor (if applicable)
- Underlayment (if finish floor)
- 1.5" to 4" thick concrete/gypcrete topping
- Acoustical mat
- WSP (if applicable)
- Mass timber floor panels



Credit: AcoustiTECH

# Acoustics & Sound Control

## Solutions Paper



### Acoustics and Mass Timber: Room-to-Room Noise Control

Richard McLain, PE, SE • Senior Technical Director • WoodWorks




T3 Minneapolis  
Architect: MGA | Michael Green Architecture, DLR Group  
Structural Engineer: Magnusson Klemencic Associates  
Design Assist • Build: StructureCraft

The growing availability and code acceptance of mass timber—i.e., large solid wood panel products such as cross-laminated timber (CLT) and nail-laminated timber (NLT)—for floor, wall and roof construction has given designers a low-carbon alternative to steel, concrete, and masonry for many applications. However, the use of mass timber in multi-family and commercial buildings presents unique acoustic challenges.

While laboratory measurements of the impact and airborne sound isolation of traditional building assemblies such as light wood-frame, steel and concrete are widely available, fewer resources exist that quantify the acoustic performance of mass timber assemblies. Additionally, one of the most desired aspects of mass timber construction is the ability to leave a building's structure exposed as finish, which creates the need for asymmetric assemblies. With careful design and detailing, mass timber buildings can meet the acoustic performance expectations of most building types.

[http://www.woodworks.org/wp-content/uploads/wood\\_solution\\_paper-MASS-TIMBER-ACOUSTICS.pdf](http://www.woodworks.org/wp-content/uploads/wood_solution_paper-MASS-TIMBER-ACOUSTICS.pdf)



#### Mass Timber Assembly Options: Walls

Mass timber panels can also be used for interior and exterior walls—both bearing and non-bearing. For interior walls, the need to conceal services such as electrical and plumbing is an added consideration. Common approaches include building a chase wall in front of the mass timber wall or installing gypsum wallboard on resilient channels that are attached to the mass timber wall. As with bare mass timber floor panels, bare mass timber walls don't typically provide adequate noise control, and chase walls also function as acoustical improvements. For example, a 3-ply CLT wall panel with a thickness of 3.07" has an STC rating of 33.\* In contrast, Figure 3 shows an interior CLT partition wall with chase walls on both sides. This assembly achieves an STC rating of 58, exceeding the IBC's acoustical requirements for multi-family construction. Other examples are included in the inventory of tested assemblies noted above.

#### Acoustical Differences between Mass Timber Panel Options

The majority of acoustically-tested mass timber assemblies include CLT. However, tests have also been done on other mass timber panel options such as NLT and dowel-laminated timber (DLT), as well as traditional heavy timber options such as tongue and groove decking. Most tests have concluded that CLT acoustical performance is slightly better than that of other mass timber options, largely because the cross-orientation of laminations in a CLT panel limits sound flanking.

For those interested in comparing similar assemblies and mass timber panel types and thicknesses, the inventory noted above contains tested assemblies using CLT, NLT, glued-laminated timber panels (GLT), and tongue and groove decking.

#### Improving Performance by Minimizing Flanking

Even when the assemblies in a building are carefully designed and installed for high acoustical performance, consideration of flanking paths—in areas such as assembly intersections, beam-to-column/wall connections, and MEP penetrations—is necessary for a building to meet overall acoustical performance objectives.




One way to minimize flanking paths at these connections and interfaces is to use resilient connection isolation and sealant strips. These products are capable of resisting structural loads in compression between structural members and connections while providing isolation and breaking hard, direct connections between members. In the context of the three methods for improving acoustical performance noted above, these strips act as decouplers. With airtight connections, interfaces and penetrations, there is a much greater chance that the acoustic performance of a mass timber building will meet expectations.



Acoustical isolation strips

Photo: Rothoblaas

# Acoustics & Sound Control

### CLT (CROSS LAMINATED TIMBER)

CLT	Insulation	Resilient Channel	Cabling	Min. Topping Depth	Sound Mat	Sound Rating			Maximum GL Fire Rating
						STC	IIC	Test Number	
2"	3" Fibre Insulation	Yes	Suspended Ceiling w/ 1/2" Sound	3/4"	Acoustical 1	58 FRC	58	F1137.00-000-00	W30
					Carpet and Pad	58 FRC	58	F1137.00-000-00	
					Carpet and Pad	58 FRC	58	F1137.00-000-00	
					Acoustical 2	58 FRC	58	F1137.00-000-00	

CLT	Insulation	Resilient Channel	Cabling	Min. Topping Depth	Sound Mat	Sound Rating			Maximum GL Fire Rating
						STC	IIC	Test Number	
2"	3" Fibre Insulation	Yes	Suspended Ceiling w/ 1/2" Sound	3/4"	Acoustical 1	58 FRC	58	F1137.00-000-00	W30
					Carpet and Pad	58 FRC	58	F1137.00-000-00	
					Carpet and Pad	58 FRC	58	F1137.00-000-00	
					Acoustical 2	58 FRC	58	F1137.00-000-00	

CLT	Insulation	Resilient Channel	Cabling	Min. Topping Depth	Sound Mat	Sound Rating			Maximum GL Fire Rating
						STC	IIC	Test Number	
2"	3" Fibre Insulation	Yes	Suspended Ceiling w/ 1/2" Sound	3/4"	Acoustical 1	58 FRC	58	F1137.00-000-00	W30
					Carpet and Pad	58 FRC	58	F1137.00-000-00	
					Carpet and Pad	58 FRC	58	F1137.00-000-00	
					Acoustical 2	58 FRC	58	F1137.00-000-00	

© 2017 KINETICS NOISE CONTROL, INC. All rights reserved. For more information, please contact your local KINETICS representative.

# Acoustics & Sound Control

## Inventory of Tested Assemblies

**Table 1: CLT Floor Assemblies with Concrete/Gypsum Topping, Ceiling Side Exposed**



CLT Panel	Concrete/Gypsum Topping	Acoustical Mat Product Between CLT and Topping	Finish Floor	STC <sup>1</sup>	IIC <sup>1</sup>	Source
CLT 5-ply (6.875")	1-1/2" Gyp-Crete*	Maxxon Acousti-Mat* 3/4	None	47 <sup>2</sup> ASTC	47 <sup>2</sup> AIIC	1
			LVT	-	49 <sup>2</sup> AIIC	
			Carpet + Pad	-	75 <sup>2</sup> AIIC	
			LVT on Acousti-Top*	-	52 <sup>2</sup> AIIC	
			Eng Wood on Acousti-Top*	-	51 <sup>2</sup> AIIC	
			None	49 <sup>2</sup> ASTC	45 <sup>2</sup> AIIC	
	1-1/2" Levelrock*	Maxxon Acousti-Mat* 3/4 Premium	LVT	-	47 <sup>2</sup> AIIC	
			LVT on Acousti-Top*	-	49 <sup>2</sup> AIIC	
		USG SAM N25 Ultra	None	45 <sup>6</sup>	39 <sup>6</sup>	15
			LVT	48 <sup>6</sup>	47 <sup>6</sup>	16
			LVT Plus	48 <sup>6</sup>	49 <sup>6</sup>	58
			Eng Wood	47 <sup>6</sup>	47 <sup>6</sup>	59
			Carpet + Pad	45 <sup>6</sup>	67 <sup>6</sup>	60
			Ceramic Tile	50 <sup>6</sup>	46 <sup>6</sup>	61
		None	None	45 <sup>6</sup>	42 <sup>6</sup>	15
			LVT	48 <sup>6</sup>	44 <sup>6</sup>	16



# Lateral System Choices & Impacts



# Lateral System Choices

## Concrete Shearwalls





# Lateral System Choices



Connection to concrete core





# Lateral System Choices

Connections to concrete core


- Tolerances & adjustability
- Drag/collector forces



PLAN VIEW



PLAN VIEW





# Lateral System Choices

## Steel Braced Frame




Photos: Marcus Kauffmann, ODF

# Lateral System Choices

Connections to steel frame

- Tolerances & adjustability
- Consider temperature fluctuations
- Ease of installation



Photos: Marcus Kauffmann, ODF



# Lateral System Choices

## Wood-Frame Shearwalls



Credit: KL&A Engineers & Builders

# Lateral System Choices

## MT Shearwalls





# Lateral System Choices

## MT Rocking Shearwalls




Photo: WoodWorks




Image: KPFF

# Lateral System Choices

## Timber Braced Frame



Credit: Alex Schreyer

# Lateral System Choices

## Prescriptive Code Compliance

Concrete Shearwalls

Steel Braced Frames

Light Wood-Frame Shearwalls

CLT Shearwalls

CLT Rocking Walls

Timber Braced Frames



**2021 SDPWS  
ASCE 7-22**






Photo: WoodWorks





# Key Early Design Decisions

## Early Design Decision Example

### 7-story, 84 ft tall multi-family building


- Parking & Retail on 1<sup>st</sup> floor, residential units on floors 2-7
- NFPA 13 sprinklers throughout
- Floor plate = 18,000 SF
- Total Building Area = 126,000 SF



# Key Early Design Decisions

## Early Design Decision Example

7-story, multi-family building, typ. floor plan:




# Key Early Design Decisions

## Early Design Decision Example

### MT Construction Type Options:

- 7 stories of IV-C
- 5 stories of IIIA over 2 stories of IA podium
- 5 stories of IV-HT over 2 stories of IA podium



Credit: Monte French Design Studio



# Key Early Design Decisions

## Early Design Decision Example

### MT Construction Type Options:

- 7 stories of IV-C
- 5 stories of IIIA over 2 stories of IA podium
- 5 stories of IV-HT over 2 stories of IA podium

### Implications of Type IV-C:

- 2 hr FRR, all exposed floor panels, beams, columns
- Likely will need at least 5-ply CLT / 2x6 NLT/DLT
- Efficient spans in the 14-17 ft range
- Efficient grids of that or multiples of that (i.e. 30x25, etc)
- No podium required
- CLT exterior walls permitted




# Key Early Design Decisions

## Early Design Decision Example

### Type IV-C Grid Options

- Option 1




# Key Early Design Decisions

## Early Design Decision Example

### Type IV-C Grid Options

- Option 1






# Key Early Design Decisions

## Early Design Decision Example

### Type IV-C Grid Options

- Option 1




# Key Early Design Decisions

## Early Design Decision Example

### Type IV-C Grid Options

- Option 2




# Key Early Design Decisions

## Early Design Decision Example

### Type IV-C Grid Options

- Option 2






# Key Early Design Decisions

## Early Design Decision Example

### Type IV-C Floor Assembly Options



Credit: Monte French Design Studio



- 2-hr FRR: 5-ply CLT (tested assembly) or 7-ply CLT (char calculations)
- STC & IIC 50 min: 2" topping (5-ply CLT) or 1.5" topping (7-ply CLT)

Note: many other acoustic mat and topping options exist, one example shown here

Note: 5-ply is most efficient for the 15-16 ft panel spans shown

# Key Early Design Decisions

## Early Design Decision Example

### MT Construction Type Options:

- 7 stories of IV-C
- 5 stories of IIIA over 2 stories of IA podium
- 5 stories of IV-HT over 2 stories of IA podium

### Implications of Type IIIA:

- 1 hr FRR
- Potential to use 3-ply or thin 5-ply CLT
- Efficient spans vary with panel thickness
- Efficient grids of that or multiples of that (i.e. 20x25, etc)
- 1 story Type IA podium required
- CLT exterior walls not permitted




# Key Early Design Decisions

## Early Design Decision Example

### Type IIIA Grid Options

- Option 1






# Key Early Design Decisions

## Early Design Decision Example

### Type IIIA Floor Assembly Options



- 1-hr FRR: 5-ply CLT (tested assembly or char calculations)
- STC & IIC 50 min: 2" topping (5-ply CLT)

Note: many other acoustic mat and topping options exist, one example shown here

Note: 5-ply is most efficient for the 15-16 ft panel spans shown

# Key Early Design Decisions

## Early Design Decision Example

### MT Construction Type Options:

- 7 stories of IV-C
- 5 stories of IIIA over 2 stories of IA podium
- 5 stories of IV-HT over 2 stories of IA podium

### Implications of Type IV-HT:

- 1 hr FRR and min. sizes
- Potential to use 3-ply or thin 5-ply CLT
- Efficient spans vary with panel thickness
- Efficient grids of that or multiples of that (i.e. 20x25, etc)
- 1 story Type IA podium required
- CLT exterior walls permitted



# Reduce Risk

## Optimize Costs

- For the entire project team, not just builders
- Lots of reference documents



## Mass Timber Cost and Design Optimization Checklists

WoodWorks has developed the following checklists to assist in the design and cost optimization of mass timber projects.

The *design optimization* checklists are intended for building designers (architects and engineers), but many of the topics should also be discussed with the fabricators and builders. The *cost optimization* checklists will help guide coordination between designers and builders (general contractors, construction managers, estimators, fabricators, installers, etc.) as they are estimating and making cost-related decisions on a mass timber project.

Most resources listed in this paper can be found on the WoodWorks website. Please see the end notes for URLs.

**First Tech Federal Credit Union – Hillsboro, OR**  
ARCHITECT:  
Hacker  
ENGINEERS:  
Kramer Gehlen & Associates,  
Equilibrium Consulting  
CONTRACTOR:  
Swinerton



**Download Checklists at**  
**[www.woodworks.org](http://www.woodworks.org)**

[www.woodworks.org/wp-content/uploads/wood\\_solution\\_paper-Mass-Timber-Design-Cost-Optimization-Checklists.pdf](http://www.woodworks.org/wp-content/uploads/wood_solution_paper-Mass-Timber-Design-Cost-Optimization-Checklists.pdf)





## Keys to Mass Timber Success:

Know Your WHY

Design it as Mass Timber From the Start

Leverage Manufacturer Capabilities

Understand Supply Chain

Optimize Grid

Take Advantage of Prefabrication & Coordination

Expose the Timber

Discuss Early with AHJ

Work with Experienced People

Let WoodWorks Help for Free

Create Your Market Distinction

# Copyright Materials

This presentation is protected by US  
and International Copyright laws.  
Reproduction, distribution, display and use of  
the presentation without written permission  
of the speaker is prohibited.

© The Wood Products Council 2022

*Funding provided in part by the Softwood Lumber Board*

**Disclaimer:** The information in this presentation, including, without limitation, references to information contained in other publications or made available by other sources (collectively “information”) should not be used or relied upon for any application without competent professional examination and verification of its accuracy, suitability, code compliance and applicability by a licensed engineer, architect or other professional. Neither the Wood Products Council nor its employees, consultants, nor any other individuals or entities who contributed to the information make any warranty, representative or guarantee, expressed or implied, that the information is suitable for any general or particular use, that it is compliant with applicable law, codes or ordinances, or that it is free from infringement of any patent(s), nor do they assume any legal liability or responsibility for the use, application of and/or reference to the information. Anyone making use of the information in any manner assumes all liability arising from such use.

# Questions? Ask us anything.



**Jessica Scarlett, EIT**

Regional Director | NC, SC, TN

(803) 616-6231

[jessica.scarlett@woodworks.org](mailto:jessica.scarlett@woodworks.org)



901 East Sixth, Thoughtbarn-Delineate Studio, Leap!Structures, photo Casey Dunn

